
Sec. 120.52.050. Monument placement.

- A. The civil engineer or land surveyor making a survey of a parcel map shall cause permanent corner monuments to be set as specified in this section Chapter 121.10.030 ~~to be set. The monuments shall be at least 18 inches long, set firmly in the ground and extending approximately three inches above the surface of the ground, shall be set at all lot corners and witness corners.~~
- B. ~~Monument materials.~~
1. ~~Preferred. Three fourths inch (inside diameter) or larger, galvanized (or cadmium plated) capped iron pipe stamped on the top of the cap with either the notation "RCE" for the registered civil engineer or "LS" for the licensed land surveyor, together with the license number of the civil engineer or land surveyor. The year date may be stamped on the cap.~~
 2. ~~Optional.~~
 - a. ~~Steel reinforcing bar five eighths inch or three fourths inch in diameter. The "RCE" or "LS" numbered brass tag to be brazed or riveted on. The use of wire to affix the tag is not acceptable;~~
 - b. ~~Drill steel seven eighths inch or larger in diameter stamped with the "RCE" or "LS" and the license numbers;~~
 - c. ~~Square or round steel bars three fourths inch or larger in diameter stamped with the notations "RCE" or "LS" and the license numbers.~~

(Prior Code, § 9624; Code 1997, § 16.52.050)