#### INDEX OF SHEETS

SHEET NO.	SHEET NAME	TITLE
1	i	TITLE SHEET
2	ii	GENERAL NOTES, ABBREVIATIONS, AND LEGE
3	iii	SHEET INDEX MAP
4	SC-1	SURVEY CONTROL AND ALIGNMENT LISTING
5	P-1	LAYOUT STA 10+00 - 14+00
6	P-2	LAYOUT STA 14+00 - 18+00
7	P-3	LAYOUT STA 18+00 - 23+00
8	D-1	CONSTRUCTION DETAILS
9	EC-1	TEMPORARY EROSION CONTROL PLAN
10	EC-2	TEMPORARY EROSION CONTROL DETAILS
11	R-1	REVEGETATION PLAN
12	PD-1	SIGNING AND PAVEMENT DELINEATION
13	PD-2	SIGNING AND PAVEMENT DELINEATION
14	PD-3	SIGNING AND PAVEMENT DELINEATION
15	S-1	GENERAL PLAN
16	S-2	INDEX TO PLANS
17	S-3	FOUNDATION PLAN
18	S-4	ABUTMENT LAYOUT
19	S-5	ABUTMENT DETAILS
20	S-6	BOARDWALK LAYOUT PLAN
21	S-7	BOARDWALK FOUNDATION PLAN
22	S-8	BOARDWALK FOUNDATION PLAN
23	S-9	BOARDWALK TYPICAL DETAILS
24	S-10	BOARDWALK RAILING
25	S-11	ROCK SLOPE PROTECTION
26	S-12	LOG OF TEST BORINGS
27	S-13	LOG OF TEST BORINGS
28	S-14	LOG OF TEST BORINGS
29	T-1	TRAFFIC CONTROL PLAN


## COUNTY OF EL DORADO, CA DEPARTMENT OF TRANSPORTATION

PROJECT PLANS FOR THE CONSTRUCTION OF THE 2022

# SAN BERNARDINO CLASS 1 BIKE TRAIL PROJECT

IN THE COUNTY OF EL DORADO, DISTRICT 5, PORTION OF SEC 29, PORTION OF EAST 1/4 SEC 30, PORTION OF SOUTH 1/4 SEC 20, T12N, R18E, MDM

> To be supplemented with 2015 Standard Plans and Specifications of the California Department of Transportation, unless otherwise noted.



SITE LOCATION VICINITY MAP COUNTY OF EL DORADO

FUNDING AGENCY

SURFACE TRANSPORTATION BLOCK GRANT TAHOE REGIONAL PLANNING AGENCY CORONAVIRUS RESPONSE AND RELIEF SUPPLEMENTAL ACT OF 2021 PROGRAM STATE TRANSPORTATION IMPROVEMENT PROGRAM

FEDERAL AID PROJECT STPL 5925(162)

SUBMITTED BY: DONALDO S. PALAROAN P.E. DATE SENIOR CIVIL ENGINEER

STATE OF CALIFORNIA NO. C66083

COUNTY OF EL DORADO DEPARTMENT OF TRANSPORTATION

SAN BERNARDINO CLASS BIKE TRAIL PROJECT TITLE

**REVISIONS** 

of the successful Bidder to obtain proper and adequate licensing for an award of the Contract shall constitute a failure to execute the Contract, and shall result in forfeiture of the Bidders security.

CONTRACTOR'S LICENSE CLASSIFICATION: Bidders shall be properly licensed to perform the Work pursuant

CONTRACTOR'S LICENSE CLASSIFICATION: Bidders shall be properly licensed to perform the Work pursuant to the State Contractor's Licensee Law (Business and Professions Code section 7000 et seq.) and shall possess a CLASS A LICENSE or equivalent combination of Classes required by the categories and type of Work included in the Contract Documents and Plans, at the time the Contract is awarded, and shall maintain a valid license through completion and acceptance of the Work including guarantee and warranty period. If the Contractor possesses a Class A license instead of the equivalent combination of Classes required by the categories and type of work included in the Contract Documents and Plans, then the Contractor or a subcontractor must also possess a CLASS C27 "Landscaping Contractor" license. Failure of the successful Bidder to other proper and adequate licensing for an award of the Contract.



DEPARTMENT OF TRANSPORTATION (DOT). IMPROVEMENT CONSTRUCTION MUST COMPLY WITH THESE PLANS AND THE 2015 CALTRANS STANDARD PLANS, UNLESS NOTED OTHERWISE. ALL REFERENCES TO THE "STANDARD SPECIFICATIONS" MEAN THE STATE OF CALIFORNIA, DEPARTMENT OF

CONSTRUCTION HOURS WILL BE WEEKDAYS BETWEEN 8:00 A.M. AND 6:30 P.M. UNLESS PRIOR APPROVAL IS RECEIVED FROM DOT.

- THE LOCATIONS AND EXTENT OF UNDERGROUND UTILITIES IN THE WORK AREA AS SHOWN ARE APPROXIMATE AND ARE NOT NECESSARILY COMPLETE. A REASONABLE EFFORT HAS BEEN MADE TO LOCATE AND DELINEATE UTILITIES BASED UPON AVAILABLE RECORDS. YOU MUST DETERMINE THE TYPE, LOCATION, SIZE, AND/OR DEPTH OF THE UTILITIES WITHIN THE WORK AREA BEFORE STARTING WORK. YOU OR ANY SUBCONTRACTOR FOR THIS CONTRACT ARE RESPONSIBLE FOR DAMAGES DUE TO THE FAILURE TO EXACTLY LOCATE AND PRESERVE UNDERGROUND UTILITIES. YOU MUST CONTACT UNDERGROUND SERVICE ALERT AT (800) 642-2444 AT LEAST 48 HOURS BEFORE ANY CONSTRUCTION. YOU ASSUME COMPLETE RESPONSIBILITY FOR DAMAGED UTILITIES.
- UNLESS SHOWN OTHERWISE, YOU ARE RESPONSIBLE FOR THE PROTECTION OF ALL EXISTING SURVEY MONUMENTS AND OTHER SURVEY MARKERS, INCLUDING CONSTRUCTION STAKES DURING CONSTRUCTION AND YOU ARE RESPONSIBLE FOR THE COST TO REPLACE ANY SUCH SURVEY MONUMENTS, MARKERS, OR STAKES.
- YOU WILL PROVIDE ALL LIGHTS, SIGNS, BARRICADES, FLAGGERS, PILOT CAR, OR OTHER DEVICES NECESSARY TO CONTROL TRAFFIC THROUGH THE JOB SITE AND FOR PUBLIC SAFETY UNDER THESE PLANS, THE STANDARD SPECIFICATIONS, AND CALIFORNIA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD).
- YOU AGREE TO ASSUME SOLE RESPONSIBILITY FOR JOB SITE CONDITIONS DURING THE COURSE OF THE WORK, INCLUDING SAFETY OF ALL PERSONS AND PROPERTY, AND FURTHER AGREE THAT THIS REQUIREMENT APPLIES CONTINUOUSLY AND IS NOT LIMITED TO NORMAL WORKING HOURS UNDER THE CONTRACT AND STANDARD SPECIFICATIONS
- THERE WILL BE NO GRADING OR LAND DISTURBANCE BETWEEN OCTOBER 15 AND MAY 1 UNLESS APPROVALS ARE OBTAINED FROM THE TAHOE REGIONAL PLANNING AGENCY (TRPA), AS PROVIDED IN THE LIMITED EXEMPTION DESCRIBED IN CHAPTER 64, SUBSECTION 64.2.B. OF THE TRPA CODE OF ORDINANCES. APPROVALS FOR GRADING BETWEEN OCTOBER 15 AND MAY 1 MUST ALSO BE OBTAINED FROM THE LAHONTAN REGIONAL WATER QUALITY CONTROL BOARD. IF REQUIRED, DOT WILL OBTAIN THESE APPROVALS.
- YOU WILL MAINTAIN A SET OF PLANS ON THE JOB SITE SHOWING "AS-CONSTRUCTED" CHANGES MADE TO DATE. UPON COMPLETION OF THE WORK, YOU WILL GIVE TO THE COUNTY A SET OF PLANS, MARKED UP TO THE SATISFACTION OF DOT, REFLECTING THE AS-CONSTRUCTED
- ALL CONTROL STATIONING AND DATA DIMENSIONING REFERENCE THE CENTERLINE OF THE FACILITY SHOWN, UNLESS NOTED OTHERWISE.
- YOU WILL NOT CLOSE OFF ANY UTILITY LINES OR OPEN VALVES OR TAKE ANY OTHER ACTION WHICH WOULD AFFECT THE OPERATION OF WATER OR SEWER SYSTEMS WITHOUT APPROVAL FROM THE SOUTH TAHOE PUBLIC UTILITY DISTRICT (STPUD). APPROVAL MUST BE REQUESTED AT LEAST 48 HOURS BEFORE INTERRUPTION OF THE UTILITY SERVICE IS REQUIRED. ANY INTERRUPTION TO ACTIVE WATER OR SEWER SERVICES, INCLUDING FIRE HYDRANTS, WHETHER INTENTIONAL OR NOT MUST BE KEPT TO A MINIMUM TIME PERIOD. IE SERVICE TO BUILDINGS IS TO BE OFF FOR MORE THAN FOUR HOURS, YOU MUST ADVISE STPUD.
- YOU ARE REQUIRED TO IMPLEMENT DUST CONTROL MEASURES TO ENSURE THAT DUST RESULTING FROM YOUR ACTIVITIES IS CONTROLLED AND COMPLIES WITH THE PROVISIONS OF SECTION 7, "LEGAL RELATIONS AND RESPONSIBILITY TO THE PUBLIC," AND SECTION 14, "ENVIRONMENTAL STEWARDSHIP," OF THE STANDARD SPECIFICATIONS, COUNTY, AND LOCAL ORDINANCES.
- YOU ARE RESPONSIBLE FOR IMPLEMENTING ALL TEMPORARY FROSION CONTROL MEASURES. THE TEMPORARY FROSION CONTROL MEASURES MUST COMPLY WITH THE TRPA "HANDBOOK OF BEST MANAGEMENT PRACTICES" AND THE STORM WATER POLLUTION PREVENTION PLAN (SWPPP).

  DOT WILL CONTACT TRPA BEFORE THE START OF THE WORK FOR A PRE-GRADE INSPECTION OF THE INSTALLED TEMPORARY EROSION CONTROL FACILITIES. YOU ARE RESPONSIBLE FOR THE MAINTENANCE AND PERFORMANCE OF THE TEMPORARY EROSION CONTROL MEASURES THROUGHOUT THE DURATION OF THE WORK.
- CONSTRUCTION LIMITS SHOWN DELINEATE THE BOUNDARIES FOR YOUR ACTIVITIES BEYOND THE COUNTY ROAD RIGHT-OF-WAY. TEMPORARY FENCE (TYPE ESA) MUST BE ERECTED ALONG THESE BOUNDARIES BEFORE WORK STARTS. VEGETATION WITHIN THESE LIMITS MUST BE PROTECTED TO THE EXTENT FEASIBLE. ALL TREES MUST BE PROTECTED UNLESS SHOWN TO BE REMOVED.
- UNLESS NOTED OTHERWISE. ALL REVEGETATION IS TO BE COMPLETED BY OTHERS
- 15. YOU WILL ONLY USE THE DESIGNATED SITES SHOWN FOR STORAGE OF EQUIPMENT AND MATERIALS. YOU ARE RESPONSIBLE FOR THE SECURITY OF EQUIPMENT AND MATERIALS.
- IT IS YOUR AND YOUR SUBCONTRACTOR(S) RESPONSIBILITY TO EXAMINE THE JOB SITE BEFORE THE OPENING OF BID PROPOSALS. YOU MUST BECOME FAMILIAR WITH THE NATURE AND LOCATION OF THE WORK AND THE GENERAL AND LOCAL CONDITIONS, PARTICULARLY THOSE AFFECTING THE AVAILABILITY OF TRANSPORTATION, THE DISPOSAL, HANDLING, AND STORAGE OF MATERIALS, AVAILABILITY OF LABOR, WATER, ELECTRICITY, ROADS. THE UNCERTAINTIES OF WEATHER, THE CONDITIONS OF THE GROUND, SURFACE AND SUBSURFACE MATERIALS. THE FOUIPMENT AND FACILITIES NEEDED FOR AND DURING THE PERFORMANCE OF THE WORK. FAILURE BY YOU OR YOUR SUBCONTRACTOR(S) TO ACQUAINT YOURSELVES WITH THE INFORMATION AVAILABLE WILL NOT RELIEVE YOU OR YOUR SUBCONTRACTOR(S) FROM RESPONSIBILITY FOR PROPERLY ESTIMATING THE DIFFICULTY AND COST OF SUCCESSFULLY PERFORMING THE WORK.
- ELEVATIONS FOR PIPE INVERTS, FLOWLINES, TOPS OF GRATES, RIMS, ETC., ARE BASED ON THE TOPOGRAPHIC INFORMATION SHOWN. YOU WILL VERIFY ALL NECESSARY SURFACE ELEVATIONS IN THE FIELD AND NOTIFY THE TD OF ANY DISCREPANCIES WHICH MIGHT AFFECT THE OPERATION OF THE NEW FACILITIES BEFORE BREAKING GROUND FOR THE INSTALLATION. DOT MUST BE CONTACTED IF ELEVATIONS ARE INCORRECT SO
- EXCEPT FOR THOSE OBTAINED BY DOT, YOU MUST OBTAIN, AT YOUR EXPENSE, ALL PERMITS, LICENSES, INSURANCE POLICIES, ETC., NECESSARY TO COMPLY WITH STATE AND LOCAL LAWS ASSOCIATED WITH THE PERFORMANCE OF THE WORK
- YOU ARE RESPONSIBLE TO REVIEW THE CONTRACT DOCUMENTS FOR SUBMITTALS REQUIRED FOR COUNTY REVIEW AND ACCEPTANCE.
- 20. THE COUNTY WILL PROVIDE CONSTRUCTION STAKING IN COMPLIANCE WITH SECTION 5-1.26 OF THE STANDARD SPECIFICATIONS.
- THE PLANS SHOW SLOPE LENGTHS FOR PIPE ROUNDED TO THE NEAREST FOOT. ALL PIPE LENGTHS AND INVERT ELEVATIONS SHOWN ON THE PLANS ARE TO THE CENTERLINE OF THE STRUCTURES TO WHICH THE PIPES ARE ATTACHED. SEE THE STANDARD SPECIFICATIONS FOR THE MAXIMUM ALLOWABLE DEFLECTION ANGLE AT EACH PIPE JOINT.
- 22. YOU ARE RESPONSIBLE TO MAINTAIN THE GRADING LIMITS AS SHOWN ON THE PLANS, DETAILS, CROSS SECTIONS, AND AS DIRECTED BY THE

Δ	DELTA = DEFLECTION ANGLE	MAT <b>'</b> L	MATERIAL
A	ARCH OR ASPEN	MISC	MISCELLANEOUS
AB	AGGREGATE BASE	MOC	MID POINT ON CURVE
ABAND	ABANDONED	MOD	MODIFIED
ABC	ARTICULATED BLOCK CHANNEL	N N	NORTH
AC	ASPHALT CONCRETE	NIC	NOT IN CONTRACT
AP	ANGLE POINT	NGVD	NATIONAL GEODETIC VERTICAL DATUM
APN	ASSESSOR'S PARCEL NUMBER	NTS	NOT TO SCALE
BC	BEGIN CURVE	OAE	OR APPROVED EQUAL
BCR	BEGIN CURB RETURN	OC OC	ON CENTER
BGN	BEGIN CORB KETOKN	OD	OUTSIDE DIAMETER
BLC.	BLANKET-LINED CHANNEL	OG	ORIGINAL GROUND
BV	BAY VIEW	OH	OVERHEAD
BVCE	BEGIN VERTICAL CURVE ELEVATION	•	OVEREXCAVATION
BVCS	BEGIN VERTICAL CURVE STATION	P	PINE
C	CEDAR	PC	POINT OF BEGINNING OF CURVE
CALCS	CALCULATIONS	PCC	PORTLAND CEMENT CONCRETE OR
CATV	CABLE TELEVISION		POINT OF COMPOUND CURVE
CC	CENTER TO CENTER	PERF	PERFORATED
CF	CUBIC FEET OR CURB FACE	PL	PROPERTY LINE
CHD	CHORD DIRECTION	PCVCE	POINT OF COMPOUND VERTICAL CURVE ELEVATION
CIR	CIRCLE	PCVCS	POINT OF COMPOUND VERTICAL CURVE STATION
Ç	CENTERLINE	POR	PORTION
ČL	CLASS OR CENTERLINE	PRVCE	POINT OF REVERSE VERTICAL CURVE ELEVATION
CLR	CLEAR	PRVCS	POINT OF REVERSE VERTICAL CURVE STATION
CO	CURB OPENING OR CLEANOUT	PP	POWER/UTILITY POLE
CO.	COUNTY	PRC	POINT OF REVERSE CURVE
CONC	CONCRETE	PROP	PROPOSED
CONST	CONSTRUCT	PT	POINT OR POINT OF TANGENCY
CMP	CORRUGATED METAL PIPE	PUE	PUBLIC UTILITY EASEMENT
CSP	CORRUGATED STEEL PIPE	PVC	POLYVINYL CHLORIDE
CT	CALTRANS OR COURT	PVIE	POINT OF VERTICAL INTERSECTION ELEVATION
CTC	CALIFORNIA TAHOE CONSERVANCY	PVIS	POINT OF VERTICAL INTERSECTION STATION
CY	CUBIC YARD	PVMT	PAVEMENT
C&G	CURB AND GUTTER	R	RADIUS
D	DEPTH	R&R	REMOVE & REPLACE
DBL	DOUBLE	RC	RELATIVE COMPACTION
DET	DETAIL	RCP	REINFORCED CONCRETE PIPE
DI	DRAINAGE INLET OR DUCTILE IRON	RD	ROAD
DIA OR Ø	DIAMETER	REF	REFERENCE
DISS	DISSIPATOR	REQ'D	REQUIRED
DR	DRIVE	RLC	ROCK-LINED CHANNEL
D/W	DRIVEWAY	ROW	RIGHT-OF-WAY
E	EAST	RSP	ROCK SLOPE PROTECTION
EA	EACH	RT	RIGHT
EC	END OF CURVE	RW	RETAINING WALL
ECR	END OF CURB RETURN	S	SOUTH OR SANITARY SEWER
ELEV	ELEVATION	SCO	SEWER CLEAN OUT
ELEC	ELECTRIC	SD	STORM DRAIN
ENGR	ENGINEER	SDMH	STORM DRAIN MANHOLE
EP	EDGE OF PAVEMENT	SED FB	SEDIMENT FOREBAY
ESA	ENVIRONMENTALLY SENSITIVE AREA	SEZ	STREAM ENVIRONMENT ZONE
ESMT	EASEMENT	SF	SQUARE FEET
EVCE	END VERTICAL CURVE ELEVATION	SHT	SHEET
EVCS	END VERTICAL CURVE STATION	SL	SLOPE LENGTH
EX OR EXIST		SMH	SEWER MANHOLE
F	FIR	ST	SEDIMENT TRAP OR STREET
FES	FLARED END SECTION	STA	STATION
FG	FINISHED GRADE	STD	STANDARD
FH	FIRE HYDRANT	STL	STEEL
FL	FLOWLINE FINISH SUBSEACE	STPUD	SOUTH TAHOE PUBLIC UTILITY DISTRICT
FS	FINISH SURFACE	SWPPP	STORM WATER POLLUTION PREVENTION PLAN
G CA	GAS	T	TELEPHONE
GA GB	GAUGE GRADE BREAK	TBC	TOP BACK OF CURB
GLS	GRASS-LINED SWALE	TBD	TOP BACK OF DIKE TOP OF DIKE
GLS	GROUND WATER	TD TBR	
H	HORIZONTAL	TG	TO BE REMOVED TOP OF GRATE
n HDPE	HIGH DENSITY POLYETHYLENE	TTL	TOTAL
IDEL	HIGH DENSHI FOLIEITILENE	TOALIO	TRANSTION

TRANS

TRM

TYP

UG

UKN

USFS

TRANSITION

UNDERGROUND

WEST OR WATER

WILLOW CLUSTER

WATER VALVE

TYPICAL

UNKNOWN

VERTICAL

WITHOUT

WITH


TURF REINFORCEMENT MAT

TAHOE REGIONAL PLANNING AGENCY

UNITED STATES FOREST SERVICE

**ABBREVIATIONS** 

NOTE: LOWER CASE TEXT WITHIN PLAN SET INDICATES EXISTING





PROPOSED

#### UTILITIES

CABLE TELEVISION NATURAL GAS ELECTRIC SEWER & WATER TELEPHONE STORM DRAIN

CHARTER COMMUNICATIONS, (775) 221-4147 SOUTHWEST GAS, (530) 543-3225 LIBERTY UTILITIES, (530) 541-6400 SOUTH TAHOE PUD, (530) 544-6474 AT&T. (530) 888-2031 CO. OF EL DORADO DOT, (530) 573-3180

REPARED UNDER THE SUPERVISION OF REGISTERED CIVIL ENGINEER

KIS KIS DSP 02/2022 MARCH 04, 2022

HWL

INCR

LTD

INTRXN

HIGH POINT

INCREASE

INTERSECTION

LINEAR FEET

LOW POINT

LEFT

INSTALL

LENGTH

HIGH WATER LINE

INVERT ELEVATION


LENGTH OF CHORD


LAKE TAHOE DATUM

INSIDE DIAMETER





COUNTY OF EL DORADO DEPARTMENT OF TRANSPORTATION SAN BERNARDINO CLASS 1 BIKE TRAIL PROJECT GENERAL NOTES, ABBREVIATIONS, AND LEGEND








NOTE: THIS PROJECT IS LOCATED IN AN ENVIRONMENTALLY SENSITIVE AREA. YOU MUST EXERCISE UTMOST CARE TO PROTECT AND MAINTAIN EXISTING VEGETATION AND MINIMIZE SOIL COMPACTION WITHIN CONSTRUCTION AREAS. !! WARNING !! THE LOCATION AND/OR ELEVATION OF EXISTING UNDERGROUND UTILITIES SHOWN ON THESE PLANS ARE ONLY APPROXIMATE. CONTRACTOR ep line (TYP) telephone line (TYP) -CONST PATH, 1 331.79 LF TO VERIFY LOCATION AND ELEVATION OF ALL TREE REMOVAL (TYP),-5 EA, THIS SHEET EXISTING UNDERGROUND UTILITIES. SALVAGE steel gate--STPUD EASEMENT (TYP) -water line (TYP) MATCH LINE~14+00 10+68.21,-SAWCUT EXISTING PAVEMENT, BGN PATH, BGN XSLOPE TRANS, FS=MATCH EX 6312.86± 1B 03402012 - June USFS BC = 10+79.45,— END XSLOPE TRANS, FS 6312.70 BC = 13+99.87,-FS 6300.57 BC = 11+65.20,-FS 6308.41 GRADING LIMITS (TYP) BC = 12+62.79,-FS 6304.03 EC = 11+27.90,-FS 6310.28 sewer (TYP) EC = 13+00.32,-FS 6302.46 EC = 11+93.20,-FS 6307.01 SCALE: HORIZ 1"= 20' VERT 1"= 5' 10+00 TO 14+00 6325 6325 6320 6320 6315 6315












REPARED UNDER THE SUPERVISION OF

KIS KIS DSP 02/2022 MARCH 04, 2022



COUNTY OF EL DORADO DEPARTMENT OF TRANSPORTATION SAN BERNARDINO CLASS 1 BIKE TRAIL PROJECT TEMPORARY EROSION CONTROL PLAN

EC-1 9 of 29 5971 95117



- 1. LOCATIONS AND LF OF TEMPORARY REINFORCED SILT FENCE REQUIRED FOR THE STAGING AREAS ARE NOT SHOWN. YOU ARE TO INCLUDE THESE AREAS IN YOUR TEMPORARY EROSION CONTROL PLAN SUBMITTAL.
- LENGTHS OF TEMPORARY REINFORCED SILT FENCE AND TEMPORARY FENCE (TYPE ESA) DOES NOT INCLUDE MINIMUM LIMITS FOR TREE PROTECTION. TREE PROTECTION FENCING IS TO BE AS SHOWN AND/OR AS DETERMINED IN THE FIELD.


DEPARTMENT OF TRANSPORTATION

DSP

MARCH 04, 2022

02/2022

SAN BERNARDINO CLASS 1 BIKE TRAIL PROJECT TEMPORARY EROSION CONTROL DETAILS



#### SYMBOL LEGEND

REVEGETATION AREA (TYPE 2) REVEGETATION AREA (TYPE 8)

STAGING AND STORAGE AREAS

#### NOTES

- REVEGETATION TYPE (1) FOR AREAS ADJACENT TO ROAD/PATH SHOULDERING, PIPE INSTALLATION, DISTURBED AREAS ADJACENT TO IMPROVEMENTS, AND GRADE TO DRAIN LOCATIONS, UNLESS NOTED OTHERWISE.
- ALL REVEGETATION AREAS DESCRIBED ABOVE WILL BE IRRIGATED WITH A WATER TRUCK BY THE COUNTY FOR TWO YEARS FOLLOWING INSTALLATION TO ENSURE OPTIMUM VEGETATION SURVIVAL.
- SEE SPECIAL PROVISIONS FOR LOCATIONS WHERE SCARIFYING IS REQUIRED PRIOR TO REVEGETATION TREATMENT.

#### REVEGETATION WORK LEGEND

TYPE (1) - STEP A: CONTRACTOR TO PLACE 2" COMPACTED TOPSOIL MIX STEP B: COUNTY TO PLACE SEED STEP C: CONTRACTOR TO APPLY 1" MULCH STEP D: CONTRACTOR TO APPLY TACKIFIER.


TYPE (2) — MEADOW AREAS: STEP A: CONTRACTOR TO LOOSEN SOIL STEP B: COUNTY TO PLACE SEED STEP C: CONTRACTOR TO APPLY TACKIFIER.

TYPE (3) - N/A.

TYPE (4) - N/A.

TYPE (7) - N/A.

TYPE (8) - STEP A: CONTRACTOR TO REGRADE TO MATCH SURROUNDING AREA. STEP B: CONTRACTOR TO PLACE 3" WOOD CHIPS.




#### TYPICAL BIKE PATH REVEGETATION

REVEGETATION SU	MMARY	AMENDMENT PER REVEGETATION TYPE					
REVEGETATION TYPE	TOTAL (SF)	REVEGETATION TYPE	HUMUS (CY)	TOPSOIL MIX (CY)	MULCH (CY)	TACKIFIER (SF)	WOOD CHIPS (CY)
TYPE (1)	14,461	TYPE (1)	23	90	45	14,461	-
TYPE (2)	18,244	TYPE (2)	-	_	-	18,244	-
TYPE (8)	1,140	TYPE (8)	-	-	-	-	11
		TOTALS	23	90	45	32,705	11




REPARED UNDER THE SUPERVISION OF





COUNTY OF EL DORADO DEPARTMENT OF TRANSPORTATION SAN BERNARDINO CLASS 1 BIKE TRAIL PROJECT REVEGETATION PLAN

11 or 29 5971 <sup>®</sup> 95117



1) FINISH ON BACK OF SIGN: MIDNIGHT GREEN ENDURA SHIELD IV, TNEMEC SEMIGLOSS HIGH BUILD ACRYLIC POLYURETHANE ENAMEL NO. 75-J7751

2) ALL TRAFFIC CONTROL DEVICES SHALL BE IN ACCORDANCE WITH THE LATEST APPROVED CALIFORNIA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (CA MUTCD).

3) ASTM DESIGNATION APPLIES TO ALL COLORS ON SIGN OR RAIL. BLACK SHALL BE NON-REFLECTIVE.

ROADWAY AND BIKE PATH SIGNS						
SIGN DESIGNATION	SIGN MESSAGE AND DESCRIPTION	SIGN SIZE	QTY	SIGN COLORS	RETROREFLECTIVE ASTM TYPE	
D11-1	"BIKE ROUTE" SIGN	24"x18"	15	WHITE ON GREEN	III	
M4-14	"BEGIN" SIGN	12"x6"	2	WHITE ON GREEN	III	
M4-6	"END" SIGN	12"x6"	2	WHITE ON GREEN	III	
M6-1	TURN ARROW SIGN	12"x9"	1	WHITE ON GREEN	III	
M6-3	"UP" ARROW SIGN	12"x9"	2	WHITE ON GREEN	III	
R44A (CA)	"NO MOTOR VEHICLES" SIGN	12"x24"	2	BLACK ON WHITE	III	

— DASHED CENTERLINE STRIPING PER CAMUTCD FIG 9C-2

PAVEMENT STRIPING				
TYPE	TYPE SHEET			
		YELLOW		
		LF		
SOLID YELLOW STRIPING	PD-1	-		
	PD-2	71		
	PD-3	-		
BROKEN YELLOW	PD-1	-		
CENTERLINE STRIPING	PD-2	507		
	PD-3	-		
	TOTAL	578		

5/16" THREAD -CORNER BOLT W/ 9/16" HEX NUT - 2.5" X 2.5" "UNISTRUT" POST OR EQUAL FINISH: MIDNIGHT GREEN ENDURA SHIELD IV, TNEMEC SEMIGLOSS HIGH BUILD ACRYLIC POLYURETHANE ENAMEL NO. 75-J7751 - 5/16" RIVET, UNISTRUT MODEL TL3806 OR EQUAL 2.5" X 2.5" X 36" "UNISTRUT" ANCHOR OR EQUAL └─2.75" X 2.75" X 18" "UNISTRUT" SLEEVE OR EQUAL SIGN DETAIL

NOTES: 1. 7' ABOVE EP.

2. LETTERING TO BE CENTERED.

3. POST SHALL BE 3' FROM EP.

BIKE PATH SIGN INSTALLATION

APPROVED FOR PAVEMENT DELINEATION AND SIGN WORK ONLY



- REMOVE AND REPLACE

REPARED UNDER THE SUPERVISION OF








COUNTY OF EL DORADO DEPARTMENT OF TRANSPORTATION SAN BERNARDINO CLASS 1 BIKE TRAIL PROJECT SIGNING AND PAVEMENT DELINEATION

PD-112 of 29 5971 95117

PD-1







# DESIGN:

## LOAD AND RESISTANCE FACTOR DESIGN

**GENERAL NOTES** 

AASHTO LRFD GUIDE SPECIFICATIONS FOR THE DESIGN OF PEDESTRIAN BRIDGES (2009), AND AASHTO LRFD BRIDGE

CONCRETE STRENGTH AND TYPE LIMITS

NO SCALE

STRUCTURAL CONCRETE, BRIDGE (3.6 KSI @ 28 DAYS)

STRUCTURAL CONCRETE, BRIDGE (4.0 KSI @ 28 DAYS)

STRUCTURAL CONCRETE, BRIDGE FOOTING (3.6 KSI @ 28 DAYS)

DESIGN SPECIFICATION (8TH EDITION) WITH CALIFORNIA AMENDMENTS, PREFACE DATED JANUARY 2014,

EXCEPT FOR BOARDWALK FOUNDATIONS

SEISMIC DESIGN: CALTRANS SEISMIC DESIGN CRITERIA (SDC), VERSION 2.0, APRIL 2019

DEAD LOAD: NO ALLOWANCE FOR FUTURE WEARING SURFACE

LIVE LOAD: H10 VEHICLE AND 90 PSF PEDESTRIAN (PED) LOADING

SNOW LOAD:

WIND LOADING: WIND LOAD IN ACCORDANCE WITH ARTICLE 3.4 OF AASHTO SPECIFICATIONS; BASIC WIND SPEED = 100 MPH

SEISMIC

SOIL PROFILE: Vs30 = 270 M/S (886 FT/S) MOMENT MAGNITUDE: Mmax = 7.5 LOAD:


PEAK GROUND ACCELERATION = 0.42g

REINFORCED CONCRETE: fy = 60 KSI

f'c = 3.6 KSI, UNLESS NOTED OTHERWISE

STRUCTURAL

TUBULAR SECTIONS: ASTM A847; fy = 50 KSI BRIDGE ANCHOR BOLTS: ASTM F1554; fy = 55 KSI STEEL:





#### CALTRANS STANDARD PLANS DATED 2018

ABBREVIATIONS (SHEET 1 OF 3) ABBREVIATIONS (SHEET 2 OF 3) A3B ABBREVIATIONS (SHEET 3 OF 3) A3C LINES AND SYMBOLS (SHEET 1 OF 5) A10A LINES AND SYMBOLS (SHEET 2 OF 5) LINES AND SYMBOLS (SHEET 3 OF 5) A10C A10D LINES AND SYMBOLS (SHEET 4 OF 5) LINES AND SYMBOLS (SHEET 5 OF 5) A10E LIMITS OF PAYMENT FOR EXCAVATION AND BACKFILL - BRIDGE



### **ACCELERATION** RESPONSE SPECTRA CURVE





REPARED UNDER THE SUPERVISION OF Mlle REGISTERED CIVIL ENGINEER


DWH SGM HECKED: 2/7/22 MSF OAD NUMBER 03/04/22 DATE:




COUNTY OF EL DORADO DEPARTMENT OF TRANSPORTATION

SAN BERNARDINO **CLASS 1 BIKE TRAIL PROJECT** 

SHEET S-2 16 of 29 95117





1 — UNDISTURBED NATIVE SOIL

— AB (CLASS 2) REINFORCED GRANULAR FILL, PLACE
IN 6" UNIFORM LIFTS AND COMPACT TO 95%

3 — TENSAR TX7 OR TX190L GEOGRID OR APPROVED EQUAL

4) — FINISH GRADE, COMPACTED TO 95% IN 8" MAX THICK LAYERS PER "STRUCTURE BACKFILL" STANDARD SPECIFICATIONS

# TYPICAL GEOSYNTHETIC REINFORCEMENT SECTION


NO SCALE

	SCOUR DATA TABLE	
SUPPORT NO.	LONG TERM (DEGRADATION AND CONTRACTION) SCOUR ELEVATION (FT)	SHORT TERM (LOCAL) SCOUR DEPTH (FT)
ABUT 1	6294.85	2.93
ABUT 2	6295.33	2.74

HYDROLOGIC SUMMARY TABLE						
DRAINAGE AREA = 39.86 SQ. MI.						
DESIGN FLOOD BASE FLOOD FLOOD OF REC						
FREQUENCY (YEARS)	50	100	1997 YEAR			
DISCHARGE (CFS)	4072.2	5168.9	5120			
WATER SURFACE ELEVATION (FT) AT BRIDGE	6297.76	6298.20	6299.73			

NOTE: FLOODPLAIN DATA BASED ON INFORMATION AVAILABLE WHEN THE PLANS WERE PREPARED AND ARE SHOWN TO MEET FEDERAL REQUIREMENTS. THE ACCURACY OF SAID INFORMATION IS NOT WARRANTED BY EL DORADO COUNTY. INTERESTED OR AFFECTED PARTIES SHOULD MAKE THEIR OWN INVESTIGATION.

SPREAD FOOTING DATA TABLE						
SUPPORT LOCATION	SERVICE PERMISSIBLE NET CONTACT STRESS (SETTLEMENT) (KSF)	STRENGTH/CONSTRUCTION FACTORED GROSS NOMINAL BEARING RESISTANCE Øb=0.45 (KSF)				
ABUT 1	8.4	6.48				
ABUT 2	8.4	6.48				



FOUNDATION PLAN SCALE : AS SHOWN

PREPARED UNDER THE SUPERVISION OF:

DESIGNED:

DWH

CHECKED:

MSF

NO. C71517

White Description

NUMBER DATE

DESIGNED:

DWH

CHECKED:

MSF

REGISTERED CIVIL ENGINEER

03/04/22


DATE:





3/4/22


COUNTY OF EL DORADO
DEPARTMENT OF TRANSPORTATION


SAN BERNARDINO CLASS 1 BIKE TRAIL PROJECT SHEET
S-3
17 OF 29
W.O. No. 95117



















## TYPICAL TREAD SPACING DETAIL



## TYPICAL SHIM/GROUT DETAIL




## TYPICAL PILE SECTION

NO SCALE

SGM

3/4/22




NOTES:

- 1. ALL HOLES TO BE DRILLED BY CONTRACTOR
- 2. ONE (1) CLIP ANGLE REQ'D AT EACH END OF EACH TREAD, TWO (2) CLIPS TOTAL PER TREAD
- ANCHORS SHALL MEET REQUIREMENTS OF ACI 355.4 INSTALL ANCHORS NO SOONER THAN 14 DAYS AFTER
- DELIVERY OF PRECAST COMPONENTS

#### TREAD TO BEAM CONNECTION

NO SCALE

NO SCALE



- SET THREADED BAR IN EPOXY ADHESIVE ANCHORING SYSTEM
- 2. MIN. 3  $\frac{1}{2}$ " THREADED BAR EMBEDMENT INTO ABUTMENT
- DRILLED HOLES SHALL BE 7/8" DIAMETER COMPLETELY COVER THREADED BAR, NUT,
- WASHER, AND ANY ADJACENT VOIDS WITH EPOXY ADHESIVE OR NON-SHRINK GROUT
- 5. RAILING NOT SHOWN FOR CLARITY

## BOARDWALK ABUTMENT DETAIL

NO SCALE

**BOARDWALK TYPICAL DETAILS** SCALE : AS SHOWN

REA UNDER THE SUPERVISION OF REGISTERED CIVIL ENGINEER


DWH HECKED: MSF \_\_\_\_\_03/04/22 DATE: DAD NUMBER





COUNTY OF EL DORADO DEPARTMENT OF TRANSPORTATION

SAN BERNARDINO CLASS 1 BIKE TRAIL PROJECT

SHEET S-9 23 OF 29 95117








CEMENTATION				
DESCRIPTION	CRITERIA			
WEAK	CRUMBLES OR BREAKS WITH HANDLING OR LITTLE FINGER PRESSURE.			
MODERATE	CRUMBLES OR BREAKS WITH CONSIDERABLE FINGER PRESSURE.			
STRONG	WILL NOT CRUMBLE OR BREAK WITH FINGER PRESSURE.			


DIST	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET No	TOTAL SHEETS
3	ED	N/A	N/A	27	29
PLA Cores 10751 Reno,	3/4/2022  NS APPROV.  (Grayslake Dr., Nevada 89521) 36-5916	IL ENGINEER	No No	73484 2-31-2022	THE PROPERTY OF THE PROPERTY O

GWS = Ground Water Surface


	BOREHOLE IDENTIFICATION					
SYMBOL	HOLE TYPE	DESCRIPTION				
Size	A AUGER BORING (HOLLOW OR SOLID STEM BUCKET)					
Size	ROTARY DRILLED BORING (CONVENTIONAL) ROTARY DRILLED WITH SELF-CASING WIRE-LINE ROTARY CORE WITH CONTINUOUSLY-SAMPLED, SELF-CASING WIRE-LINE ROTARY PERCUSSION BORING (AIR)					
Size	R RC	ROTARY DRILLED DIAMOND CORE ROTARY DRILLED DIAMOND CORE, CONTINUOUSLY SAMPLED				
HD HAND DRIVEN (1-INCH SOIL TUBE) HA HAND AUGER						
•	D	DYNAMIC CONE PENETRATION BORING				
	▲ CPT CONE PENETRATION TEST (ASTM D 5778)					
[]	O OTHER (NOTE ON LOTB)					
	Note: Size in inches.					

	CONSISTENCY OF COHESIVE SOILS						
DESCRIPTION	SHEAR STRENGTH (tsf)	POCKET PENETROMETER MEASUREMENT, PP, (tsf)	TORVANE MEASUREMENT, TV, (tsf)	VANE SHEAR MEASUREMENT, VS, (tsf)			
VERY SOFT	LESS THAN 0.12	LESS THAN 0.25	LESS THAN 0.12	LESS THAN 0.12			
SOFT	0.12 - 0.25	0.25 - 0.5	0.12 - 0.25	0.12 - 0.25			
MEDIUM STIFF	0.25 - 0.5	0.5 - 1	0.25 - 0.5	0.25 - 0.5			
STIFF	0.5 - 1	1 - 2	0.5 - 1	0.5 - 1			
VERY STIFF	1 - 2	2 - 4	1 - 2	1 - 2			
HARD	GREATER THAN 2	GREATER THAN 4	GREATER THAN 2	GREATER THAN 2			





FILE => \$REQUEST



22-0335 C 27 of 29

								SHEET S	3-13
VIMAL P. VIMALARAJ, P.E. G.E.  DESIGN OVERSIGHT	DRAWN BY	SEAN MCMICKEN	JONATHAN PAYNE	ENGINEERING SERVICES	PREPARED FOR THE COUNTY OF ELDORADO	DIVISION OF ENGINEERING	BRIDGE NO.	SAN BERNARDINO CLASS 1 BIKE TRAIL P	ROJECT
SIGN OFF DATE	CHECKED BY	VIMAL P. VIMALARAJ, P.E. G.E.	FIELD INVESTIGATION BY:   DATE: 05-21-2-19 & 05-22-2019	GEOTECHNICAL SERVICES	DEPARTMENT OF PUBLIC WORKS	DESIGN BRANCH	POST MILES	LOG OF TEST BORINGS 2	
GS CIVIL LOG OF TEST BORINGS SHEET (ENGLISH) (REV. 03/14/12)				ORIGINAL SCALE IN INCHES FOR REDUCED PLANS	1 2 3	UNIT: ENGLISH PROJECT NUMBER & PHASE: 5012-02-1	CONTRACT NO	DISREGARD PRINTS BEARING EARLIER REVISION DATES  DISREGARD PRINTS BEARING EARLIER REVISION DATES	27 29

GRAPHIC/SYMBOL GROUP NAMES			GRAPHI	C/SYMBOL	GROUP NAMES	
00000	GW GP	WELL-GRADED GRAVEL WELL-GRADED GRAVEL WITH SAND POORLY-GRADED GRAVEL		CL	LEAN CLAY LEAN CLAY WITH SAND LEAN CLAY WITH GRAVEL SANDY LEAN CLAY SANDY LEAN CLAY GRAVELLY LEAN CLAY	
	GW-GM	POORLY-GRADED GRAVEL WITH SAND  WELL-GRADED GRAVEL WITH SILT  WELL-GRADED GRAVEL WITH SILT AND SAND			GRAVELLY LEAN CLAY WITH SAND  SILTY CLAY SILTY CLAY WITH SAND SILTY CLAY WITH GRAVEL	
	GW-GC	WELL-GRADED GRAVEL WITH CLAY (OR SILTY CLAY) WELL-GRADED GRAVEL WITH CLAY AND SAND (OR SILTY CLAY AND SAND)		CL-ML	SANDY SILTY CLAY SANDY SILTY CLAY WITH GRAVEL GRAVELLY SILTY CLAY GRAVELLY SILTY CLAY WITH SAND	
0000	GP-GM	POORLY-GRADED GRAVEL WITH SILT POORLY-GRADED GRAVEL WITH SILT AND SAND		ML	SILT SILT WITH SAND SILT WITH GRAVEL SANDY SILT	
	GP-GC	POORLY-GRADED GRAVEL WITH CLAY (OR SILTY CLAY) POORLY-GRADED GRAVEL WITH CLAY AND SAND (OR SILTY CLAY AND SAND)			SANDY SILT WITH GRAVEL GRAVELLY SILT GRAVELLY SILT WITH SAND	
	GM	SILTY GRAVEL SILTY GRAVEL WITH SAND		OL	ORGANIC LEAN CLAY ORGANIC LEAN CLAY WITH SAND ORGANIC LEAN CLAY WITH GRAVEL SANDY ORGANIC LEAN CLAY	
200	GC	CLAYEY GRAVEL WITH SAND			SANDY ORGANIC LEAN CLAY WITH GRAVEL GRAVELLY ORGANIC LEAN CLAY GRAVELLY ORGANIC LEAN CLAY WITH SAND	
	GC-GM	SILTY, CLAYEY GRAVEL SILTY, CLAYEY GRAVEL WITH SAND		OL	ORGANIC SILT ORGANIC SILT WITH SAND ORGANIC SILT WITH GRAVEL SANDY ORGANIC SILT	
. A A.	SW	WELL-GRADED SAND WELL-GRADED SAND WITH GRAVEL			SANDY ORGANIC SILT WITH GRAVEL GRAVELLY ORGANIC SILT GRAVELLY ORGANIC SILT WITH SAND	
	SP SW-SM	POORLY-GRADED SAND POORLY-GRADED SAND WITH GRAVEL  WELL-GRADED SAND WITH SILT WELL-GRADED SAND WITH SILT AND GRAVEL		СН	FAT CLAY FAT CLAY WITH SAND FAT CLAY WITH GRAVEL SANDY FAT CLAY SANDY FAT CLAY WITH GRAVEL GRAVELLY FAT CLAY	
	SW-SC	WELL-GRADED SAND WITH CLAY (OR SILTY CLAY) WELL-GRADED SAND WITH CLAY AND GRAVEL (OR SILTY CLAY AND GRAVEL)		MH	GRAVELLY FAT CLAY WITH SAND  ELASTIC SILT WITH SAND ELASTIC SILT WITH GRAVEL SANDY ELASTIC SILT WITH GRAVEL	
	SP-SM	POORLY-GRADED SAND WITH SILT POORLY-GRADED SAND WITH SILT AND GRAVEL		IVIT	SANDY ELASTIC SILT SANDY ELASTIC SILT WITH GRAVEL GRAVELLY ELASTIC SILT GRAVELLY ELASTIC SILT WITH SAND	
	SP-SC	POORLY-GRADED SAND WITH CLAY (OR SILTY CLAY) POORLY-GRADED SAND WITH CLAY AND GRAVEL (OR SILTY CLAY AND GRAVEL)		ОН	ORGANIC FAT CLAY ORGANIC FAT CLAY WITH SAND ORGANIC FAT CLAY WITH GRAVEL SANDY ORGANIC FAT CLAY	
	SM	SILTY SAND SILTY SAND WITH GRAVEL			SANDY ORGANIC FAT CLAY WITH GRAVEL GRAVELLY ORGANIC FAT CLAY GRAVELLY ORGANIC FAT CLAY WITH SAND	
	SC	CLAYEY SAND CLAYEY SAND WITH GRAVEL		ОН	ORGANIC ELASTIC SILT ORGANIC ELASTIC SILT WITH SAND ORGANIC ELASTIC SILT WITH GRAVEL SANDY ORGANIC ELASTIC SILT	
	SC-SM	SILTY, CLAYEY SAND SILTY, CLAYEY SAND WITH GRAVEL			SANDY ORGANIC ELASTIC SILT WITH GRAVEL GRAVELLY ORGANIC ELASTIC SILT GRAVELLY ORGANIC ELASTIC SILT WITH SAND	
7. 7. 7. 7. 7. 7. 7. 7. 7.	PT	PEAT	(-	OL/OH	ORGANIC SOIL ORGANIC SOIL WITH SAND ORGANIC SOIL WITH GRAVEL H SANDY ORGANIC SOIL	
		COBBLES COBBLES AND BOULDERS BOULDERS	17 17 3 17 17 3 17 17 3		SANDY ORGANIC SOIL WITH GRAVEL GRAVELLY ORGANIC SOIL GRAVELLY ORGANIC SOIL WITH SAND	

SEAN MCMICKEN

VIMAL P. VIMALARAJ, P.E. G.E.

JONATHAN PAYNE

DATE: 05-21-2019 & 05-22-2019

VIMAL P. VIMALARAJ, P.E. G.E.

GS CIVIL LOG OF TEST BORINGS SHEET (ENGLISH) (REV. 03/14/12)

DESIGN OVERSIGHT

#### FIELD AND LABORATORY TESTING

- (C) CONSOLIDATION (ASTM D2435)
- (CL) COLLAPSE POTENTIAL (ASTM D4546)
- COMPACTION CURVE (CTM 216)
- CORROSIVITY TESTING (CTM 643, CTM 422, CTM 417)
- CONSOLIDATED UNDRAINED TRIAXIAL (ASTM D4767)
- DIRECT SHEAR (ASTM D3080)
- (EI) EXPANSION INDEX (ASTM D4829)
- (M) MOISTURE CONTENT (ASTM D2216)
- ORGANIC CONTENT-% (ASTM D2974)
- PERMEABILITY (CTM 220)
- (PA) PARTICLE SIZE ANALYSIS (ASTM D422)
- PLASTICITY INDEX (AASHTO T 90) LIQUID LIMIT (AASHTO T 89)
- (PL) POINT LOAD INDEX (ASTM D5731)
- (PM) PRESSURE METER
- (R) R-VALUE (CTM 301)
- (SE) SAND EQUIVALENT (CTM 217)
- (SG) SPECIFIC GRAVITY (AASHTO T 100)
- (SL) SHRINKAGE LIMIT (ASTM D4943)
- (SW) SWELL POTENTIAL (ASTM D4546)

UNCONFINED COMPRESSION-SOIL

(ASTM D2166)

UNCONFINED COMPRESSION-ROCK (ASTM D7012 - METHOD C)

- UNCONSOLIDATED UNDRAINED TRIAXIAL (ASTM D2850)
- (UW) UNIT WEIGHT (ASTM D7263 METHOD B)

	DIST	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET No	TOTAL SHEETS
	3	ED	N/A	N/A	28	29
-	PLA Cores 10751 Reno,	3/4/2022  NS APPROVIOUS Engineering, Grayslake Dr. Nevada 89521 36-5916	L ENGINEER	NO PANCE	GAM V/M3 . 73484 2-31-2022 CAL IFO	ARA J LE

APPARENT DENSITY OF COHESIONLESS SOILS					
DESCRIPTION	SPT N (BLOWS / 12 INCHES)				
VERY LOOSE	0 - 5				
LOOSE	5 - 10				
MEDIUM DENSE	10 - 30				
DENSE	30 - 50				
VERY DENSE	GREATER THAN 50				

MOISTURE				
DESCRIPTION	CRITERIA			
DRY	NO DISCERNABLE MOISTURE			
MOIST	MOISTURE PRESENT, BUT NO FREE WATER			
WET	VISIBLE FREE WATER			

PERCENT OR PROPORTION OF SOILS				
DESCRIPTION	CRITERIA			
TRACE	PARTICLES ARE PRESENT BUT ESTIMATED TO BE LESS THAN 5%			
FEW	5% - 10%			
LITTLE	15% - 25%			
SOME	30% - 45%			
MOSTLY	50% - 100%			

PARTICLE SIZE				
DES	CRIPTION	SIZE		
BOULDER		GREATER THAN 12"		
COBBLE		3" - 12"		
GRAVEL	COARSE	3/4" - 3"		
GRAVEL	FINE	1/5" - 3/4"		
	COARSE	1/16" - 1/5"		
SAND	MEDIUM	1/64" - 1/16"		
	FINE	1/300" - 1/64"		
SILT AND CLA	Y	LESS THAN 1/300"		

SHEET S-14

28 29

PREPARED FOR THE COUNTY OF ELDORADO DEPARTMENT OF PUBLIC WORKS

**ENGINEERING SERVICES** 

GEOTECHNICAL SERVICES

ORIGINAL SCALE IN INCHES FOR REDUCED PLANS

DIVISION OF ENGINEERING DESIGN BRANCH

ENGLISH


CONTRACT NO.:

SAN BERNARDINO CLASS 1 BIKE TRAIL PROJECT

LOG OF TEST BORINGS 3

PROJECT NUMBER & PHASE: FILE => \$REQUEST

22-0335 C 28 of 29



### **LEGEND**

PROPOSED STAGING AREA WITH SF

G20-2

"END ROAD WORK" SIGN

APPROXIMATE SIGN LOCATION

W20-1

"ROAD WORK AHEAD" SIGN

TRAFFIC BARRICADE

- 1. THIS PLAN HAS BEEN PREPARED AS A GUIDE FOR YOU IN PREPARATION OF A COMPLETE TRAFFIC CONTROL PLAN AND TO AID IN YOUR PLANNING FOR STAGING/STORAGE OF MATERIALS AND EQUIPMENT. YOUR TRAFFIC CONTROL PLAN WILL INCLUDE DETAILED CONTROLS INCLUDING FLAGGERS, LANE CLOSURES, AND SIGNS FOR ALL ITEMS OF ROAD WORK WHICH WILL REQUIRE ALTERATION OF EXISTING TRAFFIC PATTERNS. THE LEGEND SHOWS THE LIST OF SIGNS TO BE
- 2. YOUR TRAFFIC CONTROL PLAN WILL ADDRESS EACH PHASE OF CONSTRUCTION (e.g. PIPE PLACEMENT, STRUCTURES ADJACENT TO AND/OR AFFECTING THE ROADWAY, ETC.) AND WILL CONFORM TO PART 6 OF THE CALIFORNIA MUTCD ENTITLED "TEMPORARY TRAFFIC CONTROL" AND THE SPECIAL PROVISIONS. YOUR TRAFFIC CONTROL PLAN WILL ALSO INCLUDE ALL SIGNING REQUIRED AT INTERSECTING STREETS WITHIN THE AREA THAT WILL REQUIRE TRAFFIC CONTROL.
- 3. WHEN LANE CLOSURES ARE REMOVED AND ROADS ARE OPEN TO PUBLIC TRAFFIC, ALL DRIVEWAYS WITHIN THE WORK AREA WILL BE ACCESSIBLE AND OPERATIONAL.
- 4. YOU WILL NOT EXCAVATE MORE THAN CAN BE INSTALLED AND BACKFILLED IN ONE WORKING DAY.
- 5. YOUR ATTENTION IS DIRECTED TO THE SWPPP, TEMPORARY EROSION CONTROL SHEETS, REVEGETATION PLAN SHEET, AND THE SPECIAL PROVISIONS REGARDING TEMPORARY EROSION CONTROL REQUIREMENTS FOR STAGING AREAS.
- 6. STAGING AREAS SHOWN ARE FOR THE TEMPORARY STORAGE OF CONSTRUCTION MATERIALS AND EQUIPMENT WHICH ARE TO BE USED ON THIS PROJECT.



REPARED UNDER THE SUPERVISION OF REGISTERED CIVIL ENGINEER

KIS KIS DSP 02/2022 MARCH 04, 2022



COUNTY OF EL DORADO DEPARTMENT OF TRANSPORTATION SAN BERNARDINO CLASS 1 BIKE TRAIL PROJECT TRAFFIC CONTROL PLAN

29 of 29 CONTRACT NO. **5971** 95117