Exhibit A: RF Report



2018 MAR 29 AM 11: 37

RECEIVED PLANNING DEPARTMENT

Radio Frequency Emissions Compliance Report For AT&T Mobility

Site Name:

Short Place

Site Structure Type: Monopole

Address:

9441 Peavine Ridge Road

Latitude:

38.78483

Pollock Pines, California

Longitude:

-120.49922

Report Date: January 30, 2018

Project:

New Build

General Summary

AT&T Mobility has contracted Waterford Consultants, LLC to conduct a Radio Frequency Electromagnetic Compliance assessment of the proposed Short Place site located at 9441 Peavine Ridge Road, Pollock Pines, California. This report contains information about the radio telecommunications equipment to be installed at this site and the surrounding environment with regard to RF Hazard compliance. This assessment is based on installation designs and operational parameters provided by AT&T Mobility.

The compliance framework is derived from the Federal Communications Commission (FCC) Rules and Regulations for preventing human exposure in excess of the applicable Maximum Permissible Exposure ("MPE") limits. At any location at this site, the power density resulting from each transmitter may be expressed as a percentage of the frequency-specific limits and added to determine if 100% of the exposure limit has been exceeded. The FCC Rules define two tiers of permissible exposure differentiated by the situation in which the exposure takes place and/or the status of the individuals who are subject to exposure. General Population / Uncontrolled exposure limits apply to those situations in which persons may not be aware of the presence of electromagnetic energy, where exposure is not employment-related, or where persons cannot exercise control over their exposure. Occupational / Controlled exposure limits apply to situations in which persons are exposed as a consequence of their employment, have been made fully aware of the potential for exposure, and can exercise control over their exposure. Based on the criteria for these classifications, the FCC General Population limit is considered to be a level that is safe for continuous exposure time. The FCC General Population limit is 5 times more restrictive than the Occupational limits.

	Limits for General Populat	ion/ Uncontrolled Exposure	Limits for Occupational/ Controlled Exposure		
Frequency (MHz)	Power Density (mW/cm²)	Averaging Time (minutes)	Power Density (mW/cm²)	Averaging Time (minutes)	
30-300	0.2	30	1	6	
300-1500	f/1500	30	f/300	6	
1500-100,000	1.0	30	5.0	6	

f=Frequency (MHz)

In situations where the predicted MPE exceeds the General Population threshold in an accessible area as a result of emissions from multiple transmitters, FCC licensees that contribute greater than 5% of the aggregate MPE share responsibility for mitigation.

S 18-0007

Exhibit A: RF Report

Short Place-New Site 013018

Based on the computational guidelines set forth in FCC OET Bulletin 65, Waterford Consultants, LLC has developed software to predict the overall Maximum Permissible Exposure possible at any particular location given the spatial orientation and operating parameters of multiple RF sources. These theoretical results represent worst-case predictions as emitters are assumed to be operating at 100% duty cycle.

For any area in excess of 100% General Population MPE, access controls with appropriate RF alerting signage must be put in place and maintained to restrict access to authorized personnel. Signage must be posted to be visible upon approach from any direction to provide notification of potential conditions within these areas. Subject to other site security requirements, occupational personnel should be trained in RF safety and equipped with personal protective equipment (e.g. RF personal monitor) designed for safe work in the vicinity of RF emitters. Controls such as physical barriers to entry imposed by locked doors, hatches and ladders or other access control mechanisms may be supplemented by alarms that alert the individual and notify site management of a breach in access control. Waterford Consultants, LLC recommends that any work activity in these designated areas or in front of any transmitting antennas be coordinated with all wireless tenants.

Analysis

AT&T Mobility proposes the following installation at this location:

- Install twelve (12) antennas, four (4) per Alpha, Beta, Gamma sector
- Install nineteen (19) RRUS

The antennas will be mounted on a 160-foot monopole with centerlines at 150 and 140 feet above ground level. The antennas will be oriented toward 0, 240 and 120 degrees. The Effective Radiated Power (ERP) in any direction from all AT&T Mobility operations will not exceed 28,573 Watts. Other appurtenances such as GPS antennas, RRUs and hybrid cable are not sources of RF emissions. From this site, AT&T Mobility will enhance voice and data services to surrounding areas in licensed 700, 850, 1900, 2100 and 2300 MHz bands. No other antennas are known to be operating in the vicinity of this site.

Power density decreases significantly with distance from any antenna. The panel-type antennas to be employed at this site are highly directional by design and the orientation in azimuth and mounting elevation, as documented, serve to reduce the potential to exceed MPE limits at any location other than directly in front of the antennas. For accessible areas at ground level, the maximum predicted power density level resulting from all AT&T Mobility operations is 0.0565% of the FCC General Population limits. Incident at adjacent buildings depicted in Figure 1, the maximum predicted power density level resulting from all AT&T Mobility operations is 0% of the FCC General Population limits. The proposed operation will not expose members of the General Public to hazardous levels of RF energy and will not contribute to existing cumulative MPE levels on walkable surfaces at ground or at adjacent buildings by 5% of the General Population limits.

Waterford Consultants, LLC recommends posting RF alerting signage (Caution) at the base of the proposed monopole to inform authorized climbers of potential conditions near the antennas. These recommendations are depicted in Figure 2.

Short Place-New Site 013018





Figure 1: Antenna Locations



Page 3

Exhibit A: RF Report

Short Place-New Site 013018

Compliance Statement

Based on information provided by AT&T Mobility and predictive modeling, the installation proposed by AT&T Mobility at 9441 Peavine Ridge Road, Pollock Pines, California will be compliant with Radiofrequency Radiation Exposure Limits of 47 C.F.R. § 1.1307(b)(3) and 1.1310. RF alerting signage and restricting access to the lattice tower to authorized climbers that have completed RF safety training is required for Occupational environment compliance.

Certification

I, David H. Kiser, am the reviewer and approver of this report and am fully aware of and familiar with the Rules and Regulations of both the Federal Communications Commissions (FCC) and the Occupational Safety and Health Administration (OSHA) with regard to Human Exposure to Radio Frequency Radiation, specifically in accordance with FCC's OET Bulletin 65. I have reviewed this Radio Frequency Exposure Assessment report and believe it to be both true and accurate to the best of my knowledge.

id H. Kiser, P. E.

2018.01.30 11:36:09 -05'00'



on Behalf of



PROJECT SUPPORT STATEMENT

AT&T PROJECT NAME: CONNECT AMERICA FUND II (CAF II) PROJECT

DEVELOPMENT APPLICATION FOR AT&T SITE "SHORT PLACE"

AT&T SITE NUMBER: CVL03371

AUTHORIZED AGENT:

EPIC WIRELESS GROUP, LLC

ZONING MANAGER:

JARED KEARSLEY; 916-755-1326; jared.kearsley@epicwireless.net

PROPERTY OWNER: FRANK CASTANEDA

(530) 644-6444

APN: 009-610-22

9441 Peavine Ridge Road, Pollock Pines, CA 95726

PROJECT'S BACKGROUND AND OBJECTIVES

- SEARCH RING'S DESCRIPTION AND OBJECTIVES
- POTENTIAL CO-LOCATIONS
- **ALTERNATIVE SITE ANALYSIS**
- SUBJECT PARCEL AND SITE DETAILS AND SUPPORTING DOCUMENTS
- OPERATIONAL STATEMENT
- FIRE SUPPRESSION SYSTEM
- OTHER CONSIDERATIONS RELATING TO NEW WIRELESS TELECOMMUNICATION FACILITIES PURSUANT TO 17.14.210 AND 17.22.500 OF THE EL DORADO COUNTY ZONING CODE

S 18-0007 18-1212 D 5 of 48



on Behalf of



Project Background and objectives:

AT&T is participating in a Federal Government funded project called Connect America Fund (CAF) – which is to provide underserved areas throughout the United States in general and throughout El Dorado County in particular with hi-speed broadband internet. The build-up of hi-speed broadband internet throughout rural/underserved areas will not only drive economic growth in rural America, but will expand the online marketplace nationwide, creating jobs, educational and businesses opportunities across the country. The CAF project is required to provide broadband internet services capable of 10 Mbps download and 1 Mbps upload speeds.

AT&T has the necessary technology that allows them to build out their territory in El Dorado County with the much demanded hi-speed broadband internet to help improve the county's rural infrastructure. AT&T's basis for transmitting and receiving hi-speed broadband internet to residences is executed by providing one site with either a microwave fiber hop or a direct fiber line to the site and transferring the high speeds of fiber to each Living Unit (LU) via wireless signals. Each LU being provided with the service will have a small square antenna located in a vantage point on the property where it has a direct line of site to the tower. The square antenna will send and receive wireless broadband internet providing the LU with a minimum of 10/1 Mbps download and upload speeds, respectively.

AT&T's secondary objective is to provide and enhance AT&T's Wireless Telecommunications services (cellular services) to underserved areas. Cellular services go hand in hand with building the internet infrastructure throughout these underserved areas. People today rely on their mobile devices not only for educational and business purposes, but also for emergency services. Increasing AT&T's cellular coverage and capacity throughout El Dorado County's rural areas while providing wireless broadband internet will greatly assist with enhancing the county's economic growth and the area's infrastructure.

Given the need for direct line of site to residences, a taller than typical tower will be necessary in order to provide wireless broadband internet services to as many homes in the targeted areas as possible. During the tower design phase, the Radio Frequency (RF) engineer study many variables including surrounding tree heights, tree densities, population densities, and surrounding hill tops, in order to properly design a sufficient tower height with the goal of achieving the FCC's track census block mandates of reaching specific LU coverage objectives per area. Living Unit (LU) coverage objectives are provided by the RF engineer using density maps and are based on the area's approximate population. AT&T's goal is not only to reach the coverage objective, but to outperform the coverage objective to ensure that the maximum amount of homes are being provided this service while taking into consideration a small margin of error during the simulation process.







Search Ring's Description and Objectives:



AT&T Mobility is proposing to build and maintain an unmanned wireless telecommunication facility consisting of a 40' x 45', 1,800 square foot enclosed compound (lease area). The compound will include a 160 foot Stealth Monopine tower, one pre-manufactured equipment cabinet, and one 15KW DC standby diesel generator. This facility will be located at 9441 Peavine Ridge Road, Pollock Pines, within El Dorado County's jurisdiction in a 10.70 acre RL-10 zone. The site is approximately 1.11 miles northwest of US Highway 50 and the area consists of large "evergreen" trees, and rolling hills with rocky terrain.

AT&T's objective for the Short Place site is to provide wireless hi-speed broadband internet to the surrounding community and cellular services to the nearby residences in addition to U.S. Highway 50. Just west of the search ring is a relatively dense underserved area and to the south is U.S. Highway 50. The site location's elevation is approximately 4,011 feet while the surrounding community's elevation averages around 3,600 feet, giving the homes within the surrounding community great potential for line of site to the tower. U.S. Highway 50's average elevation is 3,200 feet, therefore, the highway's coverage will significantly increase and will enhance the safety for highway travelers. After running a coverage simulation at the site location, AT&T is anticipating meeting and beating their FCC objective for the targeted area and will fill significant coverage gaps along U.S. Highway 50.



on Behalf of



Potential Co-locations:



There is one existing tower owned by American Tower Corporation that was analyzed by AT&T's RF engineer team for a potential Co-Location. The tower is located at 9571 White Meadow Road and is approximately 1.3 miles east of the center of the Search Ring and approximately 1.75 miles east of the proposed AT&T site location. The tower is 122 feet tall with an available antenna height of 97'. If the tower was capable of being structurally modified to allow for a taller tower, an available antenna height would then be 127 feet, however, a tower modification would have to be justified with a Structural Analysis.

Provided the elevation at the existing tower is 3,740 feet and the elevation at the proposed site location is 4,011 with a difference of 271 feet, the total difference in antenna height would be 294 feet (in the event the tower was modified for a taller antenna height). Additionally, the existing tower is over a mile away from the nearest residence, therefore, this tower's coverage would not suffice for the Short Place Search Ring under the CAF II Project. Being placed above a bend in U.S. Highway 50, the existing tower was strategically located to gain great coverage over a major stretch of the Highway. Furthermore, the existing tower wasn't built to cover residences, but, primarily to capture vehicular travelers.





Connecting a Wireless World on Behalf of Alternative Site Analysis pursuant to 17.14.210 (B) (1):



Above is a map showing the Search Ring (center is the red pin), Proposed Site (green pin) and the two alternative sites (yellow pins) that were considered for placement of the telecommunications facility. Each Alternative Site is discussed below:



on Behalf of




Short Place Alternative Candidate B:

9571 White Meadow Rd., Pollock Pines, CA

Latitude/Longitude: 38.780162, -120.474362

Proposal – New Tower





Site View:





on Behalf of



Candidate B is located approximately 0.90 miles east of the center of AT&T's search ring. The proposed tower would be located on a 200 acre, TPZ zoned property owned by Sierra Pacific Industries. The property is located on the north side of White Meadow Road and the site was proposed on the south side of the property. Candidate B was chosen as AT&T's third preferred candidate as the RF Engineer's simulation yielded approximately 68% fewer LU's than the subject site located at 9441 Peavine Ridge Road. Additionally, this site covered 64% fewer LU's than the FCC requirement for the targeted area. No

known oak resources would be lost at this site location. This site would have a low visual impact on the

surrounding area given no homes are within the vicinity.



on Behalf of




Short Place Alternative Candidate C:

9571 White Meadow Rd., Pollock Pines, CA

Latitude/Longitude: 38.890607, -120.960573

Proposal – Colocation on Existing Tower



Site View:





on Behalf of



Considerations:

There is one existing tower owned by American Tower Corporation that was analyzed by AT&T's RF engineer team for a potential Co-Location. The tower is located at 9571 White Meadow Road and is approximately 1.3 miles east of the center of the Search Ring and approximately 1.75 miles east of the proposed AT&T site location. The tower is 122 feet tall with an available antenna height of 97'. If the tower was capable of being structurally modified to allow for a taller tower, an available antenna height would then be 127 feet, however, a tower modification would have to be justified with a Structural Analysis.

Provided the elevation at the existing tower is 3,740 feet and the elevation at the proposed site location is 4,011 with a difference of 271 feet, the total difference in antenna height would be 294 feet (in the event the tower was modified for a taller antenna height). Additionally, the existing tower is over a mile away from the nearest residence, therefore, this tower's coverage would not suffice for the Short Place Search Ring under the CAF II Project. Being placed above a bend in U.S. Highway 50, the existing tower was strategically located to gain great coverage over a major stretch of the Highway. Furthermore, the existing tower wasn't built to cover residences, but, primarily to capture vehicular travelers.

The Existing Tower yielded 45% less LUs than the proposed site location on 9441 Peavine Road, and 36% fewer LUs than the FCC's requirement for the targeted area. For that reason, the Existing Tower is not a viable co-locatable opportunity.





on Behalf of

Additional alternative sites considered and letters of interest sent out but received either no response by landlords or uninterested landlords included the following parcels:

9599 White Meadow Road, Pollock Pines – APN: 009-040-43-100; Owner: Robert and Deborah Kirtlan
9560 White Meadow Road, Pollock Pines – APN: 009-610-16-100; Owner: Elizabeth and Michael Murphy

Google Earth Image of Additional Alternative Sites:






on Behalf of



Actual View of the Proposed Location:

The proposed lease area is centrally located on the property. The site will not interfere with the existing use of the property and is an allowed use for the zone subject to an approval of a Conditional Use Permit. Access will be directly off of Peavine Ridge Road. The site is elevated above the surrounding area and has great potential for line of site to the community down below the subject parcel. The site isn't intrusive to nearby residents nor their view points from their properties. The nearest residence is approximately 580 feet to the east and sits 128 feet lower than the site location. The residence has foliage shielding their view to the site. The second closest residence is approximately 795 feet to the south and sits 100 feet below the site location and is divided by a hill top to hide the facility from the property. The subject Property is the most north property and is elevated the highest compared to any nearby properties, therefore, no viewpoints will be in jeopardy. Provided this site meets and exceeds the FCC's requirements for the targeted area and is aesthetically non-intrusive to the surrounding area, this is the best site location for the Short Place Search Ring.





on Behalf of



Planning Services

ritime > Government > Plannir

PARCEL DATA INFORMATION

3/28/2018

Enter Another Parcel

		STATUS			JURIS	DICTION		TAX F	ATE TAN	MAP .	ACREAGE
ON ASSESSMENT ROLL AND TAXED				COUNTY OF EL DORADO			59 - 4		PM 9/14/2	10.7	
015 GENERU	IL PLAN	LAND USE INFORMA	TION:								
LAND USE DES.	AG DIST.	ECOLOGICAL PRESERVES			MINERAL RESOURCES			MUNITY RURA GIONS CENTE			ADOPTED PLAI NAME
RR 015 ZONING	INFORM	ATION:				PL	I				
2		ESIGNATION		ESIGN CONTRO		PLANNED	DEVELOP	MENT		OTHER C	VERLAYS
004 GENERA		L-10 LAND USE INFORMA	TION:								
LAND USE DES.	AG DIST.	ECOLOGICAL PRESERVES			MINERAL RESOURCES	PLATTED LANDS		COMMUNITY F		SPECIFIC PLANS	ADOPTED PLAI
RR						PL.	†		1		1
004 ZONING	INFORM	ATION:						,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	***************************************		
Z	ONING D	ESIGNATION	T	ESIGN CONTRO	L	PLANNED	DEVELOF	MENT		OTHER C	WERLAYS
	R	E-10									
ISTRICTS:											
		FIRE	1	SD		SCHOOL				WATER	
UNASSIGNED			POLLOCK PINES					UNASSIGNED			
LOOD ZONE	INFORM	ATION (See Note below):									
FIRM PANEL NUMBER & REVISION PANE			PANEL RE	EL REVISION DATE FLOOD ZONE		ZONE	FLOOD ZONE BUFFER		UFFER	FLOODWAY	
06017C0550E PAN			PANEL N	NEL NOT PRINTED D)					
#SCFLLANE		05017C0575E		PANEL N	OT PRINTED	D		<u></u>			
			······								
		DRIAL DISTRICT	AC	PRESERVE	R	ARE PLANT MITIG	SATION AR	EA		MISSOURI FL	AT MC&FP
5	51	IF NOVASEL	i	0.000 (0.0		No					


No Eligibility Review Required

NOTE: The flood zone information presented here is based solely on data derived from the FEMA Flood information Rate Maps, and does not include data from any other flood studies.
















Land Use Map:








on Behalf of

Overhead View of Lease Area and Distances to nearby residences:




Emergency 15kw Diesel Generator and 1 Ton HVAC Noise Analysis:

Equation and Calculation Method:

The sound analysis methods and results are hypothetical only, using Sound Level and Distance calculations. These calculations do not take outside sounds, trees, hills, buildings, and other sound dampening variables into consideration, but, only raw sound levels after specific traveled distances which results in the worst case scenario for the sounds of the onsite backup generator and HVAC systems.

The use of emergency equipment is exempted from these limits per section 130.37.20(B).

Formulas to calculate the sound level L in dB (sound pressure level or sound intensity level) in dependence of the distance r.



Sound pressure level (dB) = Sound intensity level (dB)

$$L_2 = L_1 - |20 \cdot \log\left(\frac{r_1}{r_2}\right)| \qquad L_2 = L_1 - 10 \cdot \lg\left(\frac{r_1}{r_2}\right)^2$$







Sound Specifications:

- Emergency Generator Model: SD015 Generac
 - Average decibel (dBa) level at 23 feet = 65 dBa
- 1 Ton HVAC Model: HVAC MarvairSlimPacECUA12ACA
 - Average decibel (dBa) level at 30 feet = 46.5 dBa
 - HVAC is intrinsically compliant with El Dorado County's Noise Level Standards, per Table
 1 below, 130.37.060.1

Findings:

- 1. Distance to the nearest Property Line of APN 009-610-17 = 520'
 - a. Generator Decibel level at 520' = 37.91 dBa
- 2. Distance to the Residence at APN 009-610-17 = 580'
 - a. Generator Decibel level at 580' = 36.97 dBa
- 3. Distance to nearest vacant property line at APN: 009-040-49 = 153'
 - a. Generator Decibel level at 153' = 48.54 dBa

Conclusion:

After calculating all decibel levels at each nearby property line and residence, the onsite Emergency Backup Generator are <u>within</u> El Dorado County's noise level standards according to El Dorado County Title 130 Zoning and Noise Ordinance, Chapter 130.37 – Noise Standards.

Table 1 – Eldorado County Table 130.37.060.1 Noise Level Performance Standards for Noise Sensitive Land Uses Affected by Non-Transportation Sources

Noise Level	Daytir 7 a.m. – 7		Eveni 7 p.m. – 1		Nigł 10 p.m. –	
Descriptor	Community / Rural Centers	Rural Regions	Community / Rural Centers	Rural Regions	Community / Rural Centers	Rural Regions
Hourly Leq, dBA	55	50	50	45	45	40
Maximum Level, dBA	70	60	60	55	55	50



on Behalf of



Operation Statement:

This project is an AT&T Mobility unmanned Telecommunication Wireless Facility. It will consist of the following:

NEW SITE BUILD UNMANNED TELECOMMUNICATIONS FACILITY.

- 1. BRING POWER / TELCO / FIBER TO SITE LOCATION
- 2. PAVED ACCESS IMPROVEMENT FROM ROW
- 3. 40'X45' FENCED LEASE AREA
- 4. INSTALL AT&T APPROVED PRE-MANUFACTURED EQUIPMENT CABINET AND ASSOCIATED INTERIOR EQUIPMENT
- 5. ADD (1) NEW GPS UNITS
- 6. ADD 160'-0" MONOPINE
- 7. ADD (12) ANTENNAS (4) PER ALPHA, BETA, GAMMA SECTOR
- 8. ADD (19) PROPOSED (3) FUTURE RRUS
- 9. ADD (4) SURGE SUPPRESSORS
- 10. ADD (2) FUTURE 4' MICROWAVE DISHES
- 11. ADD 6'-0" HIGH CHAIN LINK FENCE W/ VYNAL SLATS
- 12. ADD 15KW DC DIESEL GENERATOR

The facility will operate 24 hours a day 7 days a week. Maintenance workers will visit the site approximately once a month. A 15 foot wide access route will be created directly from Peavine Ridge Road. There will be minimal noise from the standby generator, turning on once a week for 15 minutes for maintenance purposes and during emergency power outages. The Facility is approximately 580 feet west of a residence, and approximately 795 feet north of another. The location is surrounded by evergreen trees which will naturally stealth the facility in addition to being at a higher elevation than the surrounding neighbors. The surrounding area is covered with evergreen tree backdrops. The tower will be built to provide co-location opportunities.

Fire Suppression System:

A 15 foot wide access route will be created directly from Peavine Ridge Road with one fire "turnout" within the driveway. A Hammer Head Fire Turnaround will be proposed within the access route at the Facility. A Fire Department Knox Box will be located at the Property's access gate and at the Facility's access gate. Additionally, a 2A:20BC Rated Fire Extinguisher in a weather resistant cabinet will be mounted on the exterior wall of the proposed shelter.




on Behalf of



Conclusion:

Candidate A, 9441 Peavine Ridge Road, meets the FCC's mandated objectives for the targeted area of Short Place and is the best choice for the surrounding area. The chosen location will meet and exceed the FCC's mandated coverage objectives with providing hi-speed broadband internet to homes in the Short Place's Targeted area of El Dorado County. The Stealth Monopine Tower design has been chosen to blend into the existing surrounding environment as the least intrusive means while filling AT&T's gap in coverage. Significant Coverage Gaps will be filled along U.S. Highway 50 and the surrounding community. Existing foliage on the subject parcel and surrounding parcels yields a stealthed compound from all directions. No oak woodlands will be impacted/removed for this location. No special species or protected animals will be impacted per the biological resource assessment prepared by Sycamore Environmental Consultants, Inc.

Exhibit C: Location Map



Prepared by: Isaac Wolf Planning Services Department June 27, 2018

AT&T Short Place Monopine APN: 009-610-22

18-1212 D 23 of 48 Scale: 1:3200





Exhibit E: General Plan Map




Prepared by: Isaac Wolf Planning Services Department June 27, 2018

AT&T Short Place Monopine APN: 009-610-22

18-1212 D 25 of 48 Scale: 1:3200

Exhibit F: Zoning Map



Prepared by: Isaac Wolf June 27, 2018

APN: 009-610-22

18-1212 D 26 of 48 Scale: 1:3200

Exhibit G: Aerial Map






Prepared by: Isaac Wolf Planning Services Department July 2, 2018


Project No. S18-0007 AT&T Short Place Monopine APN: 009-610-22 650 ______Feet 18-1212 D 2720 48

2018 MAR 29 AM 11: 38 RECEIVED PLANNING DEPARTMENT **CVL03371 Zoning Propagation Map** February 06, 2018

Existing LTE 700 Coverage



Proposed LTE 700 Coverage (RC = 150')




2018 MAR 29 AM 11: 38


RECEIVED
PLANNING DEPARTMENT




Shot Point Map


S 18-0007





















SITE NUMBER: CVL03371

SITE NAME: SHORT PLACE

9441 PEAVINE RIDGE ROAD **POLLOCK PINES, CA 95726** JURISDICTION: ELDORADO COUNTY

USID: 178391 FA: 13787566

SHORT PLACE

9441 PEAVINE RIDGE ROAD

POLLOCK PINES, CA 95726

PREPARED FOR

at&t

EPIC WIPELESS GR	OUP
AT&T SITE NO	CVL03371
PROJECT NO:	
DRAWN BY:	EAS
CHECKED BY:	CES

0	SHAMIE	10 90%
n.	Olylaris	75 1004
-		-
		_



ADAPTIVE RE-USE ENGINEERING


Craig Horner, PE 84674 214-407-3184 3112 LEATHA WAY SACRAMENTO, CA 95821 craigmhorner@yahoo.com

TITLE SHEET


T-1


800-227-2600

SITE TYPE: MONOPINE / WALK-IN EQUIPMENT CABINET



S 18-000 Prepared by 1942 Welf 48 Planning Services Division





SHORT PLACE

9441 PEAVINE RIDGE ROAD

POLLOCK PINES, CA 95726

PREPARED FOR

2600 Camino Ramon, 4W850 N San Ramon, California 94583

EPIC WIRELESS

DRAWN BY:

ATAT SITE NO: CVL03371 PROJECT NO: 13787566

CHECKED BY: CES

No. 84674

ADAPTIVE RE-USE

ENGINEERING

Craig Horner, PE 84674

214-407-3184

3112 LEATHA WAY

SACRAMENTO, CA 95821

craigmhorner@yahoo.com

GENERAL NOTES

GN-1

at&t

GENERAL CONSTRUCTION NOTES:

- PUAS ARE INTENDED TO BE DAGRAMMATIC OUTLINE ONLY, UNLESS NOTED OTHERWISE. THE WORK SHALL INCLUDE TURNISHING MATERIALS, EQUIPMENT, APPURTENANCES AND LABOR NECESSARY TO COMPLETE ALL INSTALLATIONS AS INDICATED ON THE DRAWNICS.
- THE CONTRACTOR SHALL OBTAIN, IN WRITING, AUTHORIZATION TO PROCEED BEFORE STARTING WORK ON ANY ITEM NOT CLEARLY DETINED OR DEMINED BY THE CONTRACT DOCUMENTS.
- CONTRACTOR SHALL CONTACT USA (LINDERGROUND SERVICE ALERT) AT (800) 227-2600, FOR UTLITY LOCATIONS, 48 HOURS BEFORE PROCEEDING WITH ANY EXCAVATION, SITE WORK OR CONSTRUCTION.
- THE CONTRACTOR SHALL INSTALL ALL ECUPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY INDICATED OTHERWISE, OR WHERE LOCAL CODES OR RECULATIONS TAKE PROCEDURE.
- ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE COC/LIGO'S REQUIREMENTS REGARDING EARTHQUARE RESISTANCE, FOR, BUT NOT LIMITED TO, PPPRS, LIGHT FIRTURES, CELLING CPPD, NTEROR PARTITIONS, AND NEOWNICAL EQUIPMENT, ALL MORK MUST COMPLY WITH LOCAL EARTHQUARE COCKS AND REQUIREMENTS.
- REPRESENTATIONS OF TIME MOTHER DIVENTIONS FROM ON THE PLOT OF SAMMY COMMINES, SHALL NOT BE USED TO EDITIFY OR EXPRESS BEHAVIOR OF MERCHAN THE SAME THE CONTRICTION SHALL BUT SCALLY ON THE PART OF SAMEY DAWNS AND ANY PROCESSOR WITH THE BOOK IF ANY OSCIONATION OF SAME PROCESSOR SHALL SHALL BE ADMINISTRATION OF SAME PART OF SAME P
- THE BUILDING DEPARTMENT ISSUING THE PERMITS SHALL BE NOTIFED AT LEAST TWO MORKING DAYS PRIOR TO THE COMMENCEMENT OF WORK, OR AS OTHERWISE STIPULATED BY THE COCK ENFORCEMENT OFFICIAL HAVING JURISDICTION.
- 8. DO NOT EXCAVATE OR DISTURB BEYOND THE PROPERTY LINES OR LEASE LINES, UNLESS OTHERWISE NOTED.
- ALL EXISTING UTUITIES, FACILITIES, CONDITIONS, AND THEIR DIMENSIONS SHOWN ON THE PLAN HAVE BEEN PLOTTED FROM AVAILABLE ACCIONATE OF UNITED ACCIONATE CONTINUE OF UNITED SECURITY OF UNITED ACCIONATE OCCURRATE OCCURRAT
- 10. CONTRACTOR SHALL VERFY ALL EXISTING UTLITIES, BOTH HORIZONTAL AND VERTICALLY, PRIOR TO THE START OF CONSTRUCTION AN DISCREPANCES OR COURTS AS TO THE INTERPRETATION OF PLANS SOULD BE INAUDIATLY REPORTED TO THE AMOUNTED / DISABLER FOR REQUIRTION AND INSTRUCTION, AND INTERTIES WAS USED OF PROFESSION OF THE THE DESCRIPTION OF CONTROL OF CONTROL THE AMOUNTED / ENGINEER. FAILURE TO SECURE SUCH RESTRICTION MEANS CONTRACTOR WILL HAVE WORSED AT HIS/HER OWN RISK AND DEPOISE.
- All New and existing utility structures on site and in areas to be disturbed by construction shall be adjusted to finish elevations prior to find inspection of work.
- ANY DRAIN AND/OR FIELD TILE EXCOUNTERED / DISTURBED DURING CONSTRUCTION SHALL BE RETURNED TO IT'S ORIGINAL CONDITION PRIOR TO CONFILITION OF WHOM, STILL, LOCATION AND TIME OF ANY INAGERPRION DURINGS OF MATHOMATING SHALL BE ACCUPATION OF DISTURBING PROJECT, AND PLACED ON A SHEART TO MEMORIAN COMPLETION OF PROJECT, AND PLACED ON THE AMERICATE / MORRIER AND COMPLETION OF PROJECT,
- ALL TEMPORARY EXAMATORS FOR THE INSTALLATION OF FOLIDATIONS, UTILITIES, ETC., SHALL BE PROPERLY LAD BACK OR BRACED IN ACCORDANCE WITH CORRECT OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (05M) PEOUREMENTS.
- 14. INCLUDE MISC. ITEMS PER ATAT SPECIFICATIONS

APPLICABLE CODES, REGULATIONS AND STANDARDS:

SUBCONTRACTOR'S WORK SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES AS ADOPTED BY THE LOCAL AUTHORITY HAVING JURSDICTION (AND) FOR THE LOCATION.

THE EDITION OF THE ANI ADOPTED CODES AND STANDARDS IN EFFECT ON THE DATE OF CONTRACT AWARD SHALL COVERN THE DESIGN.

SUBCONTRACTOR'S WORK SHALL COMPLY WITH THE LATEST EDITION OF THE FOLLOWING STANDARDS:

- -MARKAN CORCRET INSTITUTE (ACI) 318, BALDING CODE REQUIRMANTS FOR STRUCTURE, CONCRET.

 -MARKAN KRITINE OF STEEL CONSTRUCTION (ACC), WARLA OF STEEL CONSTRUCTION, ACQ, WHITE IDDIN

 -TRECOMMAND/COME ROUTHER ASSOCIATION (AV) 2227-C, STRUCTURE, SANOWNO FOR STRUCTURE, ARTHUMA HOMER AND ARTHUMA SUPPORTED

 STRUCTURES.


 -FASTITUTE FOR ELECTRICAL WID ELECTRICALS CONCRETE (ETT.) 81, CODE FOR MEASURE CARRIER RESISTANT, GROUPD METERACE, AND DRIFT

 SUPPLICE FORTUNATE OF A CORPOR STRUCTURE (ETT.) 1100 (1999) RECOMMENDED PRICTICE FOR FORDERS, AND GROUNDING OF ELECTRICAL

 SECRETARIAL FOR THE STRUCTURE CONTRIBUTION OF THE STRUCTURE AND GROUNDING OF ELECTRICAL

 SECRETARIAL FOR THE STRUCTURE CONTRIBUTION OF THE STRUCTURE CONTRIBUTION OF
- COUNTRY OF THE PROPERTY OF SURE VOLVES IN LOW VOLVES AC POWER CIRCUITS (FOR LOCATION CRIEGORY "CS" AND THEIR STILL DEPOSITS.)
- TA 607 CONNECUL BUILDING CHOLOGIG AND BOYCON PROJECTIONS FOR TILLCONNAHICATIONS TILLCONDA CH-63 METHODY. CONFIDENT-BASINGO STITTA (1975), PRINCIPLA PROTECTION TILLCONDA CH-310 CONTROL OFFICE (1984) WINNE TILLCONDA CH-310 CONTROL CONTROL PROJECTIONS TILLCONDA CH-310 CONTROL CONTROL

- ANY AND ALL OTHER LOCAL & STATE LAWS AND FEGULATIONS
- FOR ANY CONFLICTS BETWEEN SECTIONS OF LISTED COORS AND STANDARDS RECARDING MATERIAL, METHODS OF CONSTRUCTION, OR OTHER RECURRISHINGS. THE MOST PESTIFICITIES SHALL DOMENN, WHERE THERE IS CONFLICT BETWEEN A GENERAL RECURRISHING AND A SPECIFIC RECOMBINISH. THE PSECTION RECURRISHING SHALL DOMEN.



PLYWOOD, 4'X2'.

PAINTED WHITE

6" HEIGHT (4) LAG SCREWS, 6"

GRADE

-1 96

STAPLE DETAIL

BLACK LETTERS,

WOOD POST, 4X4X8

.12" INCH DIA

STRAW BALE


36*

- STRAW BALE TYP 7.87"

10 MIL PLASTIC LINING

CONCRETE WASHOUT

SIGN DETAIL (OR EQUIV)



WET SEASON: ENTIPE PERIOD BETWEEN OCTOBER 1 THROUGH APRIL 30. CONTRACTOR SHALL ALSO IMPLEMENT WET SEASON MEASURES IF WET MEATHER IS EXPECTED DURING THE DRY SEASON PHASES OF GRADING

WHEN CLEARING AND GRUBBING ACTIVITIES OCCUR.

ROUGH: WHEN CUT AND FILE ACTIVITIES OCCUR AND THE SIE IMPROVEMENTS ARE CONSTRUCTED, INCLUDING UNDERGOOND PIPMS, STREETS, SOCRAMS, AND OTHER MAPROVEMENTS. HE STREET AND STEM MIRROVEMENTS ARE COMPLETED AND READY FOR CITY ACCEPTANCE.

FIBER ROLL NOTES:

- REPAIR OR REPLACE SPLIT, TORN UNRAYELING OR SLUMPING FIBER ROLLS. FIBER ROLLS TO BE STAKED 4' O.C. PARALLEL TO
- (E) CONTOURS.

 2. INSPECT FIBER ROLLS WHEN RAIN IS FORECAST, DURING AND FOLLOWING RAIN EVENTS, AT LEAST DAILY DURING PROLONGED RAINFALL, FOR SPECIFIC MONITORING INTERVALS REFER TO THE CURRENT VERSION OF STORM WATER "BMP" MANUAL FOR DURING THE NON-RAINY SEASON
- DOWNS THE NOV-MANY SASSM.

 SEQUENT STOLD BE REMOVED WHEN SEQUENT ACCUMULATION REACHES ONE—HALF THE DESIGNATED SEQUENT STORAGE
 OFFIN, USUALLY ONE—HALF THE DISTANCE BETWEEN THE TOP OF THE FIGER ROLL AND THE ADJACENT GROUND SURFACE.

 SEQUENTE REMOVED DURING MAINTENANCE MAY BE INCORPORATED INTO THE EARTHWORK ON THE SITE OR DISPOSED AT AN
 APPROPRIATE LOCATION.
- 4. FILTER BARRIER SHALL BE CONSTRUCTED LONG ENOUGH TO EXTEND ACROSS THE EXPECTED FLOW PATH AND AS APPROVED BY

CONSTRUCTION EROSION/SEDIMENTATION

CONTROL PLAN NOTES:

THE CONTRACTOR SHALL FOLLOW TYPICAL CUIDELINES FOR GRADING, EROSION AND SEDIMENT CONTROL FOR THE MEASURES SHOWN OR STATED ON THESE

CONTRACTOR MUST ENSURE THAT THE CONSTRUCTION SITE IS PREPARED PRIOR TO THE ONSET OF ANY STORM. CONTRACTOR SHALL HAVE ALL EROSION AND SEDIMENT CONTROL MEASURES IN PLACE FOR THE WINTER MONTHS PRIOR TO

OCTOBER 1.
ALL EROSION AND SEDMENT CONTROL MEASURES SHALL BE MAINTAINED UNTIL DISTURBED AREAS ARE STABLUZED. CHANGES TO THIS EROSION AND SEDMENT CONTROL PLAN SHALL BE MADE TO WEET FIELD CONDITIONS ONLY MITH THE APPROVAL OF OR AT THE DIRECTION OF A REPRESENTATIVE OF THE

DEPARMENT OF UNIONS.

THIS PLAN MAY NOT COVER ALL THE SITUATIONS THAT ARISE DURING CONSTRUCTION DUE TO UNIANTICIPATED FELD CONDITIONS, VARIATIONS MAY BE MADE TO THE PEAN IN THE FEELD SUBJECT TO THE APPROVAL OF OR AT THE DIRECTION OF A REPRESENTATIVE OF THE DEPARTMENT OF UTILITIES. DIRECTION OF A REPRESENTATIVE OF THE DEPARTMENT OF OTITITIES.

ALL EROSION AND SEDMENT CONTROL MEASURES SHALL BE CHECKED BEFORE DURING AND AFTER ALL STORUS TO ENSURE MEASURES ARE FUNCTIONING PROPERLY, REFER TO CURRENT VERSION OF STORMWATER "BMP" MANUAL FOR

SPECIFIC SCHEDULE PER SITE CONDITIONS.

SPECING SOMEDULE PER STIE CONSIDIONS.

COMIRACIOR SAUL MANITAN A LOC AT THE STIE OF ALL INSPECTIONS OR MANIFONNICE OF BUPS, AS WELL AS, ANY CORRECTIVE CHANGES TO THE BUPS OR REGISTRA SOS SELLANDE, PLAN.

FERSTALLING STREET, PLAN.

COMPANIENT OF THE STREET, PLAN.

COMPANIENT OF CONSTRUCTION WITH A PRIVILEGE FOR STIES OF THE CANTER STREET, PLAN.

CONSTRUCTION OF FRANCISCS. ALL COSTRUCTION OF THE CANTER STREET, PLAN.

CONSTRUCTION OF FRANCISCS. ALL COSTRUCTION TO FACULTATE

CONSTRUCTION OF FRANCISCS. ALL COSTRUCTION TO TACLITIZE THE PLAN.

CONSTRUCTION OF FRANCISCS. ALL COSTRUCTION TO TACLITIZE THE STREET OF THE PLAN.

CONSTRUCTION OF FRANCISCS. ALL COSTRUCTION THE PLANT OF THE P

CONSTRUCTION ENTRANCE (WHEN APPLICABLE) SHALL REMAIN IN PLACE UNTIL THE CONSTRUCTION IS COMPLETE.

THE CONSTRUCTION IS COUPLETE.
ALL SEQUENT DEPOSITED ON PAYED ROADWAYS SHALL BE SWEPT AT THE END 9. OF EACH MORRING DAY OR AS NECESSARY.
CONTRACTOR SHALL PLACE CRAVE BIOS AROUND ALL NEW DRAINAGE STRUCTURE OPENINGS IMMEDIATLY AFTER THE STRUCTURE OPENING IS CONSTRUCTED. IN SECS. GRAVEL BORS SHALL BE MANTANDE AND REVIAN IN

PLACE UNTIL CONSTRUCTION IS COMPLETED.

THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION THAT MILL PREVENT
TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC RICHT-OF-WAYS. THIS REQUIRE TOP DRESSING, REPAIR AND/OR CLEANOUT OF ANY MEASURES USED TO TRAP SEDMENT.

12. WHEN NECESSARY, WHEELS SHALL BE CLEANED PRIOR TO ENTRANCE ONTO PUBLIC RIGHT-OF-WAY.

PUBLIC MONTH-UF-WAT.
WHEN WASHING IS REQUIRED, IT SHALL BE DONE ON AN AREA STABLIZED WITH
CRUSHED STONE THAT DRAINS INTO AN APPROVED SEDIMENT TRAP OR

SEDIMENT BASIN, CONTRACTOR SHALL IMPLEMENT HOUSEKEEPING PRACTICES AS FOLLOWS:

SOLID WASTE MANAGEMENT PROVOE DESIGNATED WASTE COLLECTION AREAS AND CONTAINERS. ARRANGE FOR REGULAR REMOVAL AND DISPOSAL. CLEAR SITE OF TRASH INCLIDING ORGANIC DEBRIS, PACKAGING MATERIALS, SCRAP OR SURPLUS BUILDING

MATERIALS AND DOMESTIC WASTE DAILY. MATERIAL DELIVERY AND STORAGE

MARKAND LEUTERT NOT STRANGE.

PROVOE A DESCAIATED MATERIAL STORAGE AREA WITH SECONDARY
CONTAINMENT SUCH AS BERMING. STORE MATERIAL ON PALLETS AND PROMDE
COVERING FOR SCULBLE MATERIALS. RELOCATE STORAGE AREA INTO BUILDING
SHELL WHEN POSSIBLE. INSPECT AREA DALTY.

PROVIDE A DESIGNATED AREA FOR A TEMPORARY PIT TO BE LISED FOR PROVIDE A DESIGNATED AREA FOR A TEMPORARY PIT TO BE USED FOR CONCRETE TRUCK WASH-OUT. DISPOSE OF HARDENED CONCRETE OFFSIE AT NO TIME SHALL A CONCRETE TRUCK DUMP ITS WASTE AND CLEAN ITS TRUCK INTO THE CITY STORM DRAINS WA CURB AND CUTTER. INSPECT DALY TO CONTROL RUNOFF, AND WEEKLY FOR REMOVAL OF HARDENED

PAINT AND PAINTING SUPPLIES PROVDE INSTRUCTION TO EMPLOYEES AND SUBCONTRACTORS REGARDING REDUCTION OF POLLUTANTS INCLUDING MATERIAL STORAGE, USE, AND CLEAN UP. INSPECT SITE DALLY FOR EMDENCE OF IMPROPER DISPOSAL.

VEHICLE FUELING, MAINTENANCE AND CLEANING:

PROVIDE A DESIGNATE FERING AREA WITH SECONDARY CONTAINMENT SUCH AS BERMING. DO NOT ALLOW WORLE FUELING OF EOUPWENT. PROVIDE EQUIPMENT WITH DRIP PAIRS, RESTRICT ONSITE MAINTENANCE AND CLEANING OF EQUIPMENT TO A MINIMUM. INSPECT AREA DALY, HAZARDOUS WASTE MANAGEMENT:

PREVENT THE DISCHARGE OF POLLUTANTS FROM HAZARDOUS WASTES TO THE DRAINAGE SYSTEM THROUGH PROPER MATERIAL USE, WASTE DISPOSAL AND TRAINING OF EUROPEES THATARDOUS WASTE PRODUCTS COMMONLY FOUND ON-SITE INCLUDE BUT ARE NOT LIMITED TO PAINTS & SOCIENTIS, PETROEUR PROPURED, FERTILIZERS, FERRIEDES & PESTIODES, SOIL STABILIZATION PRODUCTS, AND CONCRETE CURING PRODUCTS.

15. USE "BMP'S" AT ALL PHASES OF CONSTRUCTION.

ORANE BACK SMIT FIGURE ROLLS, "SILL BARRIER AND OR BAG BILET FILTERS TO BE USED FOR BILET PROTECTION FROM CONSTRUCTION CONTAINANTS, COMPARIOTOR TO FIELD EIGHTEF ALL CONDITIONS MEREE HIS BUX AFFLY AND MAINIAND DURING THE CODINGS OF CONSTRUCTION, THIS SHALL APPLY TO THE LOCAL SILL ACTIVITY AS WELL AS ANY MEAR INEAULED EXTREMENT TO THE POUT OF SILL ACCESS AND CANTO THE PUBLIC ROLL OF AWAS, INCONSTRUCTION OFFISS MAY

EMITER ANY STORM MATER DAWN IN THE PUBLIC RIGHT OF MATS, THE CONSIDERATION LESSESS MAY BURNER ANY STORM MATER DAWN AT ANY TIME. THE CONTRACTION PAILS. HOWNIGH THIS AT ALL TIMES DURING THE CONSTRUCTION PAILS. ANY AN ALL STORED MATERIAS, INCLUDING BUT NOT HUMBED TO, EXCAVATED SOIL, JAPORTED ROOK, SAND OR GRAVEL, PAINT, CONCRETE, MODD, METAL, OR CONTAMINATED MATER SHALL BE

STORED PROPERLY TO INSURE NO DISCHARGE OF CONTAMINATES.
REMOVE DIRT, DEBRIS AND WEEDS FROM PUBLIC SIDE WALK AREAS AND STORM DRAIN SYSTEMS AND ANY CONSTRUCTION MATERIALS OR DEBRIS TO AN APPROVED LOCATION AS ON A DAILY BASIS (OR AS DIRECTED BY THE CITY ENGINEER). A CONCRETE WASHOUT SHALL BE ONSITE AT ALL TIMES. CONTRACTOR TO FIELD VERFY LOCATION, AND BEST WETHOD TO PREVENT SPILLS AND DISCHARGE OF CONCRETE / WATER CONTAMINANTS

CONTRACTOR TO FIELD IDENTIFY "BMP"S (BEST MANAGEMENT PRACTICES) PER SITE CONDITIONS, AND REFER TO CURRENT VERSION OF STORMWATER "BMP" MANUAL FOR SPECIFIC SCHEDULES OF DETAILS NOT SPECIFIED IN THIS PLAN

STORM WATER QUALITY NOTES:

CONTRACTOR SHALL PROMDE DRAIN INLET PROTECTION FOR ALL CATCH BASINS LOCATED IN THE VICINITY OF WORK, THIS INCLUDES ANY CATCH BASINS IN THE PUBLIC RICHT-OF-WAY, AS WELL AS ANY ON-SITE CATCH BASINS ON PRIVATE PROPERTY.

CONTRACTOR SHALL INSTALL A STABILIZED CONTRACTOR SHALL INSTALL A STABILIZED CONSTRUCTION ENTRANCE/CORESS FROM PROJECT SITE TO PREVENT TRACK-OUT OF SEDIMENT ONTO THE PUBLIC RICHT-OF WAY FROM CONSTRUCTION

CONTRACTOR SHALL ENSURE THAT CONSTRUCTION ACTIVITIES DO NOT DEPOSIT SEDIMENT ONTO THE PUBLIC ROADWAY, SIDEWALKS AND GUTTERS, ALL SEDIMENT AND CONSTRUCTION DEBRIS MUST BE REMOVED BY THE END OF EACH WORKING DAY. CONTRACTOR SHALL USE STREET SWEEPING OR OTHER DRY SWEEPING WETHOO, AS NECESSARY, TO REMOVE CONSTRUCTION OR

DEMOLITION-RELATED SEDIMENT FROM PUBLIC SIDEWALKS CULTIERS AND ROADWAY

SUEWALKS, GUTIERS AND ROADWAY, COMTRACTOR SHALL SCHEDULE WORK FOR DRY-WEATHER DAYS WHEN NO RAIN IS IN THE IMMEDIATE FORCAST.
COMTRACTOR SHALL INSTALL AN APPROVED WASH-OLD ISSTULUTIES AT THE CONSTRUCTION SITE. ALL CONCRETE, PAINT, STUCCO AND OTHER LOUDS WILL BE WASHED OUT IS NOT HIS AREA COMTRACTOR SHALL PROVIDE DUST CONTROL TO PREVENT THE MUSANCE OF BLOWNED DUST CONTROL TO WITHOUT CAUSING SEQUENT, DEBRIS, OR UTIER TO ENTIRE THE ARM YSTORU DARM SYSTEM.

IMPLEMENTATION AND ADHERENCE TO THE LOCAL

TICHTLY ARUT

GRAVEL BAG

1 CONCRETE WASHOUT DETAIL TO ENTER THE ANY STORM DRAIN SYSTEM.
CONTRACTOR SHALL INSTALL ANY OTHER BUPS
AS NECESSARY TO CONTROL THE DISCHARGE OF
POLLUTANTS FROM THE PROJECT SITE.
THE CONTRACTOR SHALL BE RESPONSIBLE FOR WOOD OR METAL STAKE SPACED O FIRER ROLL ROADWAY 4" MIN DRAIN INLET NOTE: WHEN LAYING FIBER ROLLS END TO END INSURE THEY ARE ABUTTED TIGHTLY TOGETHER EDGE OF PAVEMENT TO AVOID SEDIMENT SEEPACE

STAPLES, (2) PER BALE -

-- 10' MIN --

NOT TO SCALE

TYPE "ABOVE GRADE"

WITH STRAW BALES

NOTES:

1. ACTUAL LAYOUT DETERMINED IN THE FIELD.

2. THE CONCRETE WASHOUT SIGN SHALL BE INSTALLED WITHIN

32' OF THE TEMPORARY CONCRETE WASHOUT FACILITY.


(2) PER BALE

NATIVE MATERIAL

STAKE TYP

(OPTIONAL)

2 DRAIN INLET DETAIL 3 FIBER ROLL DETAIL



1. WOVEN WIRE FENCE TO BE FASTENED SECURELY POSTS: STEEL EITHER T OR U TO FENCE POSTS WITH WIRE TIES OR STAPLES.

MINNUM LENGIH - 5 FEET

FILTER CLOTH TO BE FASTENED SECURELY TO WOVEN WIRE FENCE WITH TIES SPACED EVERY 24" AT TOP AND MID SECTION.

WHEN TWO SECTIONS OF FILTER CLOTH ADJOIN EACH OTHER THEY SHALL BE OVER-LAPPED BY SIX INCHES AND FOLDED.

4. MAINTENANCE SHALL BE PERFORMED AS NEEDED AND MATERIAL REMOVED WHEN "BULDGES" DEVELOP IN THE SILT FENCE.

FENCE: WOVEN WIRE, 14 GA.
6" MAX. MESH OPENING.
AS DIRECTED BY MARYLAND DCR FILTER CLOTH: FILTER X, MIRAFI 100X' STABILINKA T140N OR

APPROVED EQUAL PREFARRICATED UNIT: GEOFAR ENVIROFENCE OR APPROVED

4 TYPE C SILT FENCE DETAIL







craigmhorner@ychoo.com

EROSION CONTROL NOTES & DETAILS

C-3

